

Part Number: 173310345

**Product Description :** 0.50mm Pitch Premo-Flex FFC Jumper with Ears, Same Side Contacts (Type A), 76.00mm Cable Length, Gold (Au) Plating, 45 Circuits

Series Number: 17331 **Status:** Active

**Product Category:** Flexible Printed Circuit

(FPC) Flex Jumpers

#### **Documents & Resources**

**Drawings** 

Drawing 173310345\_sd.pdf

**Specifications** 

Product Specification 173310001-001.pdf

### **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |  |
|--------------------|---|--|
| China RoHS         | Not Reviewed per SJ/T 11365-2006                  |  |
| EU ELV             | Not Relevant                                      |  |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                   |  |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |  |
| EU RoHS            | Compliant per EU 2015/863                         |  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### **EU RoHS Certificate of Compliance**

## **Part Details**

### General

| Status         | Active  |  |
|----------------|---|--|
| Category       | Flexible Printed Circuit (FPC) Flex<br>Jumpers  |  |
| Series         | 17331   |  |
| Description    | 0.50mm Pitch Premo-Flex FFC<br>Jumper with Ears, Same Side<br>Contacts (Type A), 76.00mm Cable<br>Length, Gold (Au) Plating, 45<br>Circuits |  |
| Comments       | Contacts on the same side, Type A   |  |
| Product Family | FFC Cable Jumpers, Premo-Flex<br>Flat-Flexible Cable Jumpers  |  |
| Product Name   | Premo-Flex FFC Jumper   |  |
| UPC            | 198282267898  |  |

## Electrical

| Current - Maximum per Contact | 0.55A  |
|-------------------------------|--------|
| Voltage - Maximum             | 60V AC |

# Physical

| Cable Length                  | 76.00mm            |
|-------------------------------|--------------------|
| Circuits (Loaded)             | 45                 |
| Contact Layout Type           | A (same side)      |
| Design Feature                | Superior Retention |
| Material - Plating Mating     | Gold               |
| Packaging Type                | Bag                |
| Pitch - Mating Interface      | 0.50mm             |
| Temperature Range - Operating | -40° to +105°C     |
| Wire/Cable Type               | Flat Flex Cable    |
| Wire Size (AWG)               | N/A                |

# Mates With / Use With

# Mates with Part(s)

| Description | Part Number |
|-------------|-------------|
|-------------|-------------|

| Λ / |       | \ A /: | حاد |
|-----|-------|--------|-----|
| IV  | lates | VVI    | Ln  |

Intermateable with Hirose TF31

This document was generated on Jul 01, 2024