

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: FIT600
Page 1 of 2 Pages

Issue: 4
Issue Date: 11/12/2008
Effective Date: 11/12/2008

A. Construction

- | | |
|--------------------|------------------------|
| 1) Tubing Type | Heat Shrinkable Tubing |
| 2) Tubing Material | Chlorinated Polyolefin |
| 3) Color(s) | BLACK |
| 4) Dimension | See Table 1 |

Table 1

Part Number	Minimum Supplied ID	Maximum Recovered ID	Nominal Recovered Wall Thickness
FIT600-1/4	0.250	0.143	0.035 +/- .010
FIT600-3/8	0.375	0.211	0.040 +/- .010
FIT600-1/2	0.500	0.286	0.048 +/- .015
FIT600-5/8	0.625	0.357	0.052 +/- .015
FIT600-3/4	0.750	0.428	0.057 +/- .015
FIT600-7/8	0.875	0.500	0.065 +/- .020
FIT600-1IN	1.000	0.570	0.070 +/- .020
FIT600-1 1/4	1.250	0.714	0.087 +/- .020
FIT600-1 1/2	1.500	0.857	0.095 +/- .020
FIT600-1 3/4	1.750	1.000	0.107 +/- .020
FIT600-2IN	2.000	1.140	0.110 +/- .020
FIT600-3IN	3.000	1.710	0.125 +/- .020

B. Industry Approvals

- | | |
|-----------------------------------|-------------------------------|
| 1) Other | AMS-DTL-23053/1 Class 1 and 2 |
| 2) EU Directive 2002/95/EC(RoHS): | |

All materials used in the manufacture and packaging of this part meet the requirement of EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

C. Physical & Mechanical Properties

- | | | |
|------------------------------|----------------------|-----------------|
| 1) Temperature Range | -75 to 120°C | |
| 2) Shrink Ratio | 1.75:1 | |
| 3) Full Recovery Temperature | 130°C | AMS-DTL-23053/1 |
| 4) Tensile Strength | 1500psi, Min | ASTM D638 |
| 5) Elongation | 250%, Min | ASTM D638 |
| 6) Heat Shock (200°C, 4hrs) | no cracking | AMS-DTL-23053/1 |
| 7) Longitudinal Shrinkage | +1, -10% | AMS-DTL-23053/1 |
| 8) Water Absorption | 1.00%, Max | ASTM D570 |
| 9) Specific Gravity | 1.30, Max | ASTM D792 |
| 10) Shelf Life | 1 Years @ 18 to 35°C | AMS-DTL-23053/1 |

D. Electrical Properties

- | | | |
|------------------------|--------------------------------|-----------|
| 1) Dielectric Strength | 300 V/mil, Min | ASTM D876 |
| 2) Volume Resistivity | 1x10 ¹¹ ohm-cm, Min | ASTM D876 |

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: FIT600
Page 2 of 2 Pages

Issue: 4
Issue Date: 11/12/2008
Effective Date: 11/12/2008

E. Other

1) Packaging

See Table 2

Table 2

Alpha P/N	Put Up
FIT600-1/4	150 FT
	25 FT
FIT600-3/8	150 FT
	25 FT
FIT600-1/2	150 FT
	25 FT
FIT600-5/8	150 FT
	25 FT
FIT600-3/4	100 FT
	25 FT
FIT600-7/8	100 FT
	25 FT
FIT600-1IN	100 FT
	25 FT
FIT600-1 1/4	100 FT
	25 FT
FIT600-1 1/2	100 FT
	25 FT
FIT600-1 3/4	100 FT
	25 FT
FIT600-2IN	75 FT
	25 FT
FIT600-3IN	50 FT
	25 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.