



ICPLM452, ICPLM453

DESCRIPTION

The ICPLM452 and ICPLM453 devices each consists of an infrared emitting diode optically coupled to a high speed integrated photo detector. A separate connection of the photodiode bias and output transistor collector increases the speed by several orders of magnitude over conventional phototransistor couplers by reducing the base-collector capacitance.

These devices belong to Isocom Compact Range of optocouplers.

FEATURES


- High speed 1Mbit/s
- Half Pitch 1.27mm
- Common Mode Transient Immunity 15kV/ μ s min (ICPLM453)
- High AC Isolation Voltage 3750V_{RMS}
- Guaranteed Performance from 0°C to 70°C
- Operating Temperature Range from -40°C to 85°C
- Pb Free and RoHS Compliant
- Safety Approvals Pending

APPLICATIONS

- Line Receivers
- Field Bus Communication and Control
- Power Transformer Isolation in Motor Drives
- Replacement for Low Speed phototransistor Couplers
- High Speed Logic Ground isolation
- Analog Signal Ground Isolation

ORDER INFORMATION

- Available in Tape and Reel with 3000pcs per reel.



1. Anode
3. Cathode
4. GND
5. Vout
6. Vcc

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C)

Input Diode

Forward Current	25mA
Peak Forward Current (50% Duty Cycle, 1ms P.W)	50mA
Peak Transient Current ($\leq 1\mu$ s P.W., 300pps)	1A
Reverse Voltage	5V
Power dissipation	45mW

Output

Output Current	8mA
Peak Output Current	16mA
Output Voltage	-0.5 to 20V
Supply Voltage	-0.5 to 30V
Power Dissipation	100mW

Total Package

Isolation Voltage	3750V _{RMS}
Operating Temperature	-40 to 85 °C
Storage Temperature	-55 to 125 °C
Lead Soldering Temperature (10s)	260°C

ISOCOM COMPONENTS 2004 LTD

Unit 25B, Park View Road West, Park View Industrial Estate
Hartlepool, Cleveland, TS25 1UD, United Kingdom
Tel: +44 (0)1429 863 609 Fax : +44 (0)1429 863 581
e-mail: sales@isocom.co.uk
<http://www.isocom.com>

ISOCOM COMPONENTS ASIA LTD

Hong Kong Office,
Block A, 8/F, Wah Hing Industrial mansion,
36 Tai Yau Street, San Po Kong, Kowloon, Hong Kong.
Tel: +852 2995 9217 Fax : +852 8161 6292
e-mail sales@isocom.com.hk



ICPLM452, ICPLM453

ELECTRICAL CHARACTERISTICS ($T_A = 0^\circ\text{C}$ to 70°C unless otherwise specified)

INPUT

Parameter	Symbol	Test Condition	Min	Typ.*	Max	Unit
Forward Voltage	V_F	$I_F = 16\text{mA}$		1.45	1.8	V
Reverse Voltage	V_R	$I_R = 10\mu\text{A}$, $T_A = 25^\circ\text{C}$	5.0			V
Temperature Coefficient of V_F	$\Delta V_F / \Delta T_A$	$I_F = 16\text{mA}$		-1.6		mV/ $^\circ\text{C}$

OUTPUT

Parameter	Symbol	Test Condition	Min	Typ.*	Max	Unit
High Level Supply Current	I_{CCH}	$I_F = 0\text{mA}$, $V_O = \text{Open}$, $V_{CC} = 15\text{V}$, $T_A = 25^\circ\text{C}$		0.05	1	μA
		$I_F = 0\text{mA}$, $V_O = \text{Open}$, $V_{CC} = 15\text{V}$			2	
Low Level Supply Current	I_{CCL}	$I_F = 16\text{mA}$, $V_O = \text{Open}$, $V_{CC} = 15\text{V}$		100	200	μA

COUPLED

Parameter	Symbol	Test Condition	Min	Typ.*	Max	Unit
Current Transfer Ratio	CTR	$I_F = 16\text{mA}$, $V_O = 0.4\text{V}$, $V_{CC} = 4.5\text{V}$, $T_A = 25^\circ\text{C}$	20		50	%
		$I_F = 16\text{mA}$, $V_O = 0.5\text{V}$, $V_{CC} = 4.5\text{V}$	15			
High Level Output Current	I_{OH}	$I_F = 0\text{mA}$, $V_O = V_{CC} = 5.5\text{V}$, $T_A = 25^\circ\text{C}$		0.001	0.5	μA
		$I_F = 0\text{mA}$, $V_O = V_{CC} = 15\text{V}$, $T_A = 25^\circ\text{C}$		0.001	1	
		$I_F = 0\text{mA}$, $V_O = V_{CC} = 15\text{V}$			50	
Low Level Output Voltage	V_{OL}	$I_F = 16\text{mA}$, $I_O = 3\text{mA}$, $V_{CC} = 4.5\text{V}$, $T_A = 25^\circ\text{C}$			0.4	V
		$I_F = 16\text{mA}$, $I_O = 2.4\text{mA}$, $V_{CC} = 4.5\text{V}$			0.5	

* Typical values at $T_A = 25^\circ\text{C}$



ICPLM452, ICPLM453

ELECTRICAL CHARACTERISTICS ($T_A = 0^\circ\text{C}$ to 70°C unless otherwise specified)

Switching Characteristics ($V_{CC} = 5\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ.*	Max	Unit
Propagation Delay Time to Logic Low	T_{PHL}	$I_F = 16\text{mA}$, $R_L = 1.9\text{k}\Omega$, $T_A = 25^\circ\text{C}$		0.4	0.8	μs
		$I_F = 16\text{mA}$, $R_L = 1.9\text{k}\Omega$,			1.0	
Propagation Delay Time to Logic High	T_{PLH}	$I_F = 16\text{mA}$, $R_L = 1.9\text{k}\Omega$, $T_A = 25^\circ\text{C}$		0.35	0.8	μs
		$I_F = 16\text{mA}$, $R_L = 1.9\text{k}\Omega$,			1.0	ns
Common Mode Transient Immunity at Logic High	CM_H	ICPLM452 $I_F = 0\text{mA}$, $R_L = 1.9\text{k}\Omega$, $V_{CM} = 10\text{Vp-p}$, $T_A = 25^\circ\text{C}$	5000			$\text{V}/\mu\text{s}$
		ICPLM453 $I_F = 0\text{mA}$, $R_L = 1.9\text{k}\Omega$, $V_{CM} = 1500\text{Vp-p}$, $T_A = 25^\circ\text{C}$	15000			
Common Mode Transient Immunity at Logic Low	CM_L	ICPLM452 $I_F = 16\text{mA}$, $R_L = 1.9\text{k}\Omega$, $V_{CM} = 10\text{Vp-p}$, $T_A = 25^\circ\text{C}$	5000			$\text{V}/\mu\text{s}$
		ICPLM453 $I_F = 16\text{mA}$, $R_L = 1.9\text{k}\Omega$, $V_{CM} = 1500\text{Vp-p}$, $T_A = 25^\circ\text{C}$	15000			

* Typical values at $T_A = 25^\circ\text{C}$

CM_H – The maximum tolerable rate of rise of the common mode voltage dV_{CM}/t , to ensure the output will remain in the HIGH state (i.e., $V_{OUT} > 2.0\text{V}$).

CM_L – The maximum tolerable rate of fall of the common mode voltage to dV_{CM}/t , to ensure the output will remain in the LOW output state (i.e., $V_{OUT} < 0.8\text{V}$).



ICPLM452, ICPLM453




Fig 1 Forward Current vs Forward Voltage




Fig 2 Output Current vs Output Voltage




Fig 3 Normalized CTR vs Forward Current




Fig 4 Normalized CTR vs T_A




Fig 5 Propagation Delay vs Load Resistance




Fig 6 Propagation Delay vs T_A



ICPLM452, ICPLM453




Fig 7 Logic High Output Current vs T_A




Fig 8 Frequency Response



ICPLM452, ICPLM453





Fig 9 Switching Time Test Circuit





Fig 10 Common Mode Transient Immunity Test Circuit

Common mode transient immunity in logic high level is the maximum tolerable (positive) dV_{CM}/dt on the leading edge of the common mode pulse signal V_{CM} , to assure that the output will remain in a logic high state (i.e., $V_O > 2.0V$).

Common mode transient immunity in logic low level is the maximum tolerable (negative) dV_{CM}/dt on the trailing edge of the common mode pulse signal, V_{CM} , to assure that the output will remain in a logic low state (i.e., $V_O < 0.8V$).




ICPLM452, ICPLM453

ORDER INFORMATION

ICPLM452, ICPLM453			
After PN	PN	Description	Packing quantity
None	ICPLM452, ICPLM453	Surface Mount Tape & Reel	3000 pcs per reel

DEVICE MARKING




ICPLM600 denotes Device Part Number (ICPLM452 is used as example)
Y denotes 1 digit Year code
WW denotes 2 digit Week code
/ denotes Isocom




ICPLM452, ICPLM453

PACKAGE DIMENSIONS (mm)





RECOMMENDED PAD LAYOUT (mm)






ICPLM452, ICPLM453

TAPE AND REEL PACKAGING



Direction of feed from reel




Dimension No.	A0	A1	B0	D0	D1	E	F
Dimension (mm)	6.2±0.1	4.1±0.1	5.28±0.1	1.5±0.1	1.5±0.3	1.75±0.1	5.5±0.1
Dimension No.	P0	P1	P2	t	W	K0	K0
Dimension (mm)	4.0±0.1	8.0±0.1	2.0±0.1	0.4±0.1	12.0 +0.3/-0.1	3.7±0.1	0.3±0.1



ICPLM452, ICPLM453

IR REFLOW SOLDERING TEMPERATURE PROFILE
(One Time Reflow Soldering is Recommended)



Profile Details	Conditions
Preheat <ul style="list-style-type: none"> - Min Temperature (T_{SMIN}) - Max Temperature (T_{SMAX}) - Time T_{SMIN} to T_{SMAX} (t_s) 	150°C 200°C 60s - 120s
Soldering Zone <ul style="list-style-type: none"> - Peak Temperature (T_P) - Liquidous Temperature (T_L) - Time within 5°C of Actual Peak Temperature (T_P - 5°C) - Time maintained above T_L (t_L) - Ramp Up Rate (T_L to T_P) - Ramp Down Rate (T_P to T_L) 	260°C 217°C 30s 60s - 100s 3°C/s max 6°C/s max
Average Ramp Up Rate (T _{smax} to T _P)	3°C/s max
Time 25°C to Peak Temperature	8 minutes max



DISCLAIMER

ISOCOM is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing ISOCOM products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such ISOCOM products could cause loss of human life, bodily injury or damage to property.

In developing your designs, please ensure that ISOCOM products are used within specified operating ranges as set forth in the most recent ISOCOM products specifications.

__ The ISOCOM products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These ISOCOM products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury (“Unintended Usage”). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation Instruments, traffic signal instruments, combustion control instruments, medical Instruments, all types of safety devices, etc.. Unintended Usage of ISOCOM products listed in this document shall be made at the customer’s own risk.

__ Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.

__ The products described in this document are subject to the foreign exchange and foreign trade laws.

__ The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by ISOCOM Components for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of ISOCOM Components or others.

__ The information contained herein is subject to change without notice.