

MICRO-EDGE

TE Internal #: 5822030-4

SIMM Sockets, Vertical Module Orientation, 80 Position, -67 – 221 °

F [-55 – 105 °C]

View on TE.com >



Connectors > Socket Connectors > Memory Sockets > SIMM Sockets



Module Orientation: Vertical

Number of Positions: 80

Operating Temperature Range: -55 – 105 °C [-67 – 221 °F]

Features

Product Type Features

Product Type Features	
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Keys	1
Number of Rows	1
Module Orientation	Vertical
Number of Positions	80
Body Features	
Latch Material	Brass
Retention Post Location	Center
Latch Plating Material	Nickel
Connector Profile	Standard
Contact Features	
Memory Socket Type	Memory Card
	200 μin
Contact Mating Area Plating Material	Tin

Nickel

Contact Underplating Material



PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	1 A
Termination Features	
Insertion Style	Cam-In
Termination Post & Tail Length	3.05 mm, 3.66 mm[.12 in][.144 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Polarization	Left
Mating Alignment Type	Center Post
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	LCP (Liquid Crystal Polymer)
Centerline (Pitch)	1.27 mm[.05 in]
Dimensions	
Center Retention Hole Diameter	2.45 mm[.096 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	45
Packaging Method	Box & Tube, Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought









Documents

Product Drawings

80 ME .050 VERT M/L PB-FREE



English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_5822030-4_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_5822030-4_B.3d_igs.zip

English

Customer View Model

ENG_CVM_5822030-4_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

MICRO-EDGE SIMM (Single In-Line Memory Module) Connectors

English