

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of KRM55WC71E107MH13# from the official website of Murata

"#"at the end indicates the package specification code.

# KRM55WC71E107MH13L

















< List of part numbers with package codes > KRM55WC71E107MH13L KRM55WC71E107MH13K



### **Applications**

Please be sure to read and comply with	
these "Precautions for use."	
Consumer equipment,Industrial	
Equipment,Mobile Electronics,Medical	
equipment [GHTF A/B/C] except for	
implant equipment	
Please refer to Our Website and	
specifications, etc. for information about	
the performance, functions, quality,	
management, and safety required for	
the above applications, and use	
Products after confirming the	
performance and reliability of the actual	
Product.	



### References


		Standard
Packaging	Specifications	Packing
		Quantity
L	180Embossed Tape	200
K	330Embossed Tape	500

Mass (typ.)	
1 piece	0.9g



## Appearance & Shape





1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# KRM55WC71E107MH13L

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of KRM55WC71E107MH13# from the official website of Murata

"#"at the end indicates the package specification code.



## Specifications

Length	6.1±0.5mm
Width	5.3±0.2mm
Thickness	6.4±0.3mm
Capacitance	100μF ±20%
Metal terminal width e	1.2±0.2mm
Operating Temperature Range	-55°C to 125°C
Rated Voltage	25Vdc
Capacitance change rate	±22%
Temperature characteristics (complied standard)	X7S(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

