

Part Number: 2249340003

Series Number: 224934

**Product Category:** Terminal Blocks and

Barrier Strip

Product Description: 15.00mm Pitch Lever Activated Fixed Mount PCB Terminal Block, 35° Wire Entry, Left Rear Terminal, 3 Circuits

Status: Active

**Engineering Number:** MX-TLM-705AA-15-03

#### **Documents & Resources**

### **Drawings**

Drawing 2249340003\_sd.pdf

#### 3D Models and Design Files

3D Model 2249340003\_stp.zip

### **Specifications**

Packaging Specification 1302270418-000.pdf

## **Product Environment Compliance**

## Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

# **Part Details**

## General

Status	Active
Category	Terminal Blocks and Barrier Strip
Series	224934
Description	15.00mm Pitch Lever Activated Fixed Mount PCB Terminal Block, 35° Wire Entry, Left Rear Terminal, 3 Circuits
Application	Wire-to-Board
Component Type	One Piece
Product Family	Terminal Blocks & Barrier Strips
Product Name	Lever Activated Fixed Mount
Туре	PCB Terminal Blocks and Connectors
UPC	196823649592

## Electrical

Current - Maximum per Contact	66.0A
Voltage - Maximum	600V

# Physical

3
3
Green
35° Angle
None
Copper Alloy
Tin
Tin
Polyamide
4.600/kg
1

Orientation	Vertical
Panel Mount	No
PC Tail Length	3.60mm
PCB Thickness - Recommended	2.00mm
Pitch - Mating Interface	15.00mm
Pitch - Termination Interface	15.00mm
Polarized to Mating Part	N/A
Stackable	No
Temperature Range - Operating	-40° to +115°C
Termination Interface Style	Through Hole
Wire Size (AWG)	4, 6, 8, 10, 12, 14, 16, 18
Wire Size mm²	1.24-5.89

This document was generated on Aug 27, 2024