



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	24 V DC
Product or component type	Uninterruptible power supply (UPS)
Output voltage	24 V DC
Battery type	VRLA
Provided equipment	User manual

### Batteries & Runtime

Battery location	Battery cabinet
Device mounting	DIN rail
Battery voltage	24 V

### Physical

Colour	Metal grey
Height	129 Mm
Width	192 Mm
Depth	119 Mm
Net weight	4.5 Kg
Mounting preference	No preference
USB compatible	No

### Output

Battery capacity	4.5 Ah
------------------	--------

### Conformance

Standards	IEC 62368-1
Product certifications	CE[RETURN]TÜV

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environmental

Ambient air temperature for operation	-15...50 °C
Operating altitude	0...3000 m
Relative humidity	0...95 %
Ambient air temperature for storage	-15...70 °C
Storage altitude	0...3000 M
Storage Relative Humidity	0...95 %

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	234.7 Mm
Package 1 Width	190 Mm
Package 1 Length	188 Mm
Package 1 Weight	4.8 Kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Logistical informations

Country of origin	CN
-------------------	----

## Contractual warranty

Warranty	1 Year
----------	--------

Product Life Status : **Commercialised**