



Features

- 10 Functions
- 6000 Counts Display
- Auto & Manual Ranging
- Bandwidth : 45Hz ~ 1kHz
- Variable Frequency Device (VFD)
- Duty Cycle : 0.1% ~ 99.9%
- Diode Test: Around 3V
- NCV: $\geq 100V_{rms}$
- Auto Power Off : Around 15 minutes
- Continuity Buzzer Test
- Low Battery Indications: $\leq 2.5V$
- Data Hold
- Relative Mode
- LCD Backlight
- Input Protection: 600Vrms
- Input Impedance for DC Voltage: 1G Ω Max.

Electrical Specifications

Parameters	Range	Best Accuracy
DC Voltage (V)	60mV/600mV/6V/60V/600V	$\pm(0.5\% + 2 \text{ digits})$
AC Voltage (V)	60mV/600mV/6V/60V/600V	$\pm(0.8\% + 3 \text{ digits})$
DC Current (A)	600 μ A/6000 μ A/60mA/600mA/6A/10A	$\pm(0.7\% + 2 \text{ digits})$
AC Current (A)	600 μ A/6000 μ A/60mA/600mA/6A/10A	$\pm(1\% + 3 \text{ digits})$
Resistance (Ω)	600 Ω /6k Ω /60k Ω /600k Ω /6M Ω /60M Ω	$\pm(0.8\% + 2 \text{ digits})$
Capacitance (F)	9.999nF/99.99nF/999.9nF/9.999 μ F/99.99 μ F/999.9 μ F/9.999mF/ 99.99mF	$\pm(4\% + 5 \text{ digits})$
Frequency (Hz)	10Hz - 10MHz	$\pm(0.1\% + 4 \text{ digits})$
Temperature ($^{\circ}$ C)	-40 $^{\circ}$ C to +1000 $^{\circ}$ C	$\pm(1.0\% + 3 \text{ digits})$
Temperature ($^{\circ}$ F)	-40 $^{\circ}$ F to +1832 $^{\circ}$ F	$\pm(1.5\% + 5 \text{ digits})$

General Characteristics

Power	: AA1.5 \times 2
LCD Size	: 58mm \times 36mm
Colour	: Green & Grey
Safety Rating	: CAT II 600V
Weight	: 370g
Size	: 175mm \times 81mm \times 48.5mm

Accessories	Qty.	Note
Operating Manual	1 piece	-
Test Leads	1 pair	Leads length: 900mm, Rod length: 115mm Tip length: 18mm Safety level: CAT III 1000V/CAT IV 600V 10A
Temp Probe	1 piece	Crosshead socket type thin line 1m K-type -50 to +260 $^{\circ}$ C
Battery	2 pieces	1.5V AA, replaceable

Part Number Table

Description	Part Number
True RMS Digital Multimeter	72-7780

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.