

QP50-6 TO

Description

Low dark current quadrant PIN photodiode with 4 x 12 mm² active area. Metal can type hermetic TO8S package with clear glass window.

Features

- 50 mm² Quadrant PIN detector
- High sensitivity
- Low dark current

Applications


- Laser beam position sensor
- Autocollimators
- Optical tweezers
- Ellipsometers

RoHS

2011/65/EU

2015/863/EU


[CLICK HERE >](#)
CONNECT WITH A SPECIALIST




Absolute maximum ratings

Symbol	Parameter	Min	Max	Unit
T _{STG}	Storage temp	-55	125	°C
T _{OP}	Operating temp	-40	100	°C
V _{max}	Max reverse voltage		20	V
I _{PEAK}	Peak DC current		10	mA

Spectral response (23 °C)




Schematic




Electro-optical characteristics @ 23 °C

Symbol	Characteristic	Test Condition	Min	Typ	Max	Unit
	Number of elements		4 quadrants			
	Active area		diameter 7980 (total)			µm
	Active area	per element	12			mm ²
	Gap	between elements	42			µm
I _D	Dark current	V _R = 10 V; per element		2.0	5.0	nA
C	Capacitance	V _R = 0 V; per element		120		pF
		V _R = 10 V; per element		20		pF
	Responsivity	λ = 632 nm		0.4		A/W
		λ = 900 nm		0.64		A/W
t _R	Rise time	V _R = 0 V; λ = 850 nm; R _L = 50 Ω		2000		ns
		V _R = 10 V; λ = 850 nm; R _L = 50 Ω		40		ns
	Shunt Resistance	V _R = 5 mV; per element		50		MΩ
	N.E.P.	V _R = 5 V; λ = 900 nm; per element		4 E-14		W/√Hz
V _{BR}	Breakdown voltage	I _R = 2 µA	20	50		V


Quantum efficiency (23 °C)



Capacitance as fct of reverse bias (23 °C; per element)



Dark current as fct of bias (23 °C; per element)



QP50-6 TO

Optical inspection

Optical inspection according to failure catalogue for optical sensors FK INS 201.

Package dimension:

Small quantities: Foam pad, boxed (12 cm x 16.5 cm)

Handling precautions:

- Soldering temperature max. 260 °C for 10 s. The device must be protected against solder flux vapor.
- Minimum pin length is 2 mm.
- For ESD protection standard precautionary measures are sufficient.
- For further questions please refer to document "Instructions for handling and processing".

Disclaimer: Due to our strive for continuous improvement, specifications are subject to change within our PCN policy according to JESD46C.

Ordering information (standard configurations)

Description	TE Part Number	MPQ
QP50-6 TO (TO8S)	3004334-F	1000 pcs

[CLICK HERE >](#)
CONNECT WITH A SPECIALIST

NORTH AMERICA
Tel +1 800 522 6752

EUROPE
Tel +31 73 624 6999

ASIA
Tel +86 0400 820 6015

te.com/sensors

TE Connectivity, TE, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2021 TE Connectivity Corporation. All Rights Reserved.

Version # 07/2022

