

# 2 Channel PC Based Oscilloscopes with Signal Generator

**multicomp** PRO

**RoHS  
Compliant**



## Features

- Dual-channel, ultra-thin body design.
- 100MHz bandwidth and 1GS/s real-time sampling rate.
- Standard built-in 5MHz signal generator.
- 8-bit vertical resolution, more accurate measurement.
- Max. 10M record length.
- Friendly UI, X-Y and waveform can be displayed on the same screen.
- Standard SCPI protocol supported, LabVIEW supported.
- Secondary development supported on Windows, Linux, Android, and iOS platform.
- USB Type-C powered, faster data transmission, support 5-15V wide voltage power supply.
- WiFi wireless transmission, more convenient to use. (Need to choose Wi-Fi accessories)

## Specifications

Bandwidth	100MHz	
Channel	2CH scope + 1CH function generator	
Sample Rate	1GS/s	
Rise Time	≤3.5 ns	
Horizontal Scale	2ns/div - 100s/div, step by 1 - 2 - 5	
Sampling Mode	Sample, Peak Detect, Average	
Record Length	10M	
Input Coupling	DC, AC, ground	
Input Impedance	1 MΩ ± 2%, in parallel with 15 pF ± 5 pF	
Vertical Sensitivity	2mV/div~5V/div	
Vertical Resolution (A/D)	8bits	
Max Input Voltage	40 V (DC + AC Peak)	
Probe Attenuation Factor	1X~10X~100X~1000X	
Channel Isolation	50Hz: 100 : 1, 10MHz: 40 : 1	
Interpolation	Sin(x)/x	
Vertical Range	±2 V (2 mV/div – 50 mV/div);	
	±20 V (100 mV/div – 500m V/div);	
	±40 V (1 V/div – 5 V/div)	
LF Respond (AC, -3dB)	≥10Hz (at input, AC coupling, -3dB)	
Trigger Type	Edge, Video, Slope, Pulse	
Line/Field Frequency (video)	Supported Standards: NTSC, PAL and SECAM Broadcast Systems	
Trigger Mode	Auto, Normal, Single	
Lissajous Figure	Bandwidth	Full Bandwidth
	Phase Difference	±3 degrees
Automatic Measurement	Vpp, Vmax, Vmin, Vtop, Vbase, Vamp, Vavg, Vrms, Overshoot, Preshoot, Freq, Period, Rise Time, Fall Time, Delay A→B, Delay A←B, +Width, -Width, +Duty, -Duty	

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
sg.element14.com/b/multicomp-pro

**multicomp** PRO

## 2 Channel PC Based Oscilloscopes with Signal Generator

**multicomp** PRO

Communication Interface	USB Device (type-C), USB host (Wi-Fi extension supported), LAN
Power Consumption	≤8W
Dimensions (W × H × D)	190mm×120mm×18mm

Function Generator Part	
Standard Waveforms	Sine (0.1 Hz - 5 MHz), Square (0.1 Hz-200 kHz), Ramp (1 Hz-10 kHz), Pulse (1 Hz-10 kHz)
Frequency Output	5 MHz
Sampling Rate	25 MS/s
Channel	1
Vertical Resolution	10bits
Amplitude Range	10mVpp - 5Vpp
DC Offset Range (AC+DC)	±2.5V
DC Offset Range (AC+DC)	±2.5V
Output Impedance	50 Ω (typical)

General Part	
Communication Interface	USB device (type-C), USB host (Wi-Fi extension supported), LAN
Wi-Fi Module	available in option
Power Source	5 - 15 VDC / 1.2A
Power Consumption	≤ 8 W
Device Dimension	w/h/d 190 x 120 x 18 mm
Weight	0.38 kg

**Accessories Included** : 2 x Passive Probe, Type-C Cable, Quick Guide, AC-DC Adapter with US or EU/UK Power Cord, BNC/Q9 Cable And CD

**Standard Warranty** : 03 years

### Part Number Table

Description	Part Number
PC Based Oscilloscope, 2 Channel, 8-Bits, 100MHz, 1GS/s	MP720646 US
PC Based Oscilloscope, 2 Channel, 8-Bits, 100MHz, 1GS/s	MP720646 EU-UK

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
sg.element14.com/b/multicomp-pro

**multicomp** PRO