Electro Mechanical Buzzer





Specifications

Rated Voltage : 220V AC

Operating Voltage : 160V AC to 260V AC

Rated Current (Max.) : 30mAMin. Sound Output at 10cm : 80dBCoil Resistance : $6500\Omega \pm 10\%$

Tab Material : Brass

Operating Temperature : -30°C to +70°C Storage Temperature : -40°C to +85°C

Weight : 18g

Housing Material : PBT (White)

Measuring Method (Buzzer Mode)

Test Condition

Standard

Temperature : $25^{\circ}\text{C} \pm 3^{\circ}\text{C}$ Relative Humidity : $60\% \sim 70\%$

Atmospheric Pressure : 860mbar to 1060mbar

Judgement


Temperature : 15° C ~ 35° C Relative Humidity : 45% ~ 85%


Atmospheric Pressure : 860mbar to 1060mbar.

Standard Test Fixture

Rated Voltage : 220V AC

Diagram





1.	Coil Part
2.	Terminal
3.	Vibrator
4.	Iron Core Pillar

Part Number Table

Dimensions : Millimetres Tolerance: ±0.5mm

Description	Part Number
Electro Mechanical Buzzer, 160V AC to 260VAC, 88dB	ABI-019-RC

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

