



LEAK DETECTOR SPRAY

**Gas leak detection system in aerosol form.
Specially formulated fluid, designed specifically to identify even the smallest, positive pressure, gaseous leak. ROCOL Leak Detector Spray leaves a thin uniform film of surface-active agents that accurately identify any leaks or bleeding of joints.**

FEATURES

- Ø Suitable for use with most gases
- Ø Low chlorine content to ensure maximum plastic compatibility
- Ø Compatible with most metals and plastics
- Ø Aerosol enables fast and easy application
- Ø Convenient and accurate in difficult to reach areas
- Ø No wastage or spillage
- Ø For use by *CORGI* registered Gas Installers - meets the product specification given in IGE/UP/1B Edition 2
- Ø Meets the oxygen compatibility requirements of MIL-PRF-25567E

DIRECTIONS FOR USE

- Ø Shake can well before use
- Ø Spray from a distance of 25 to 30 cm onto the area to be tested
- Ø Bubbles in the applied film indicate the location of a leak
- Ø Test compatibility with painted or coated surfaces, plastics and rubbers prior to application.

Technical and Safety Data Sheets are available from:

Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue Jan-07f

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



LEAK DETECTOR SPRAY

TECHNICAL DATA (typical values)

Appearance	Clear liquid
Base type	Aqueous blend of surfactants
Viscosity range (Brookfield)	60 – 80 cPs
Chloride content	<3 ppm
Ammonia content	<1 ppm
Propellant	CO ₂
Flash point	None
pH	9
Suitable for use with these common industrial gases	
	Natural & Town Gas
	Compressed air
	Butane / propane
	Acetylene
	Chlorine gas
	Hydrogen
	Oxygen
Storage	Storage area should be out of direct sunlight. Storage temperature should be kept below 50 °C.
Pack sizes	300ml - p/c 32030

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.