


Wiha Voltage Testers. For Professionals and Do-It-Yourselfers.



Wiha offers a universal product range of voltage testers for professionals and do-it-yourselfers. All Wiha Voltage Testers are manufactured to VDE specifications and DIN Standards as well as bearing the VDE-GS Mark.

Therefore, product safety with regard to electrical, mechanical, thermal and other risks is secured. The CE-Mark documents the conformity to the current EU-guidelines.





- Wide product range for every application
- Manufactured according to current VDE specifications and DIN Standards
- · GS-Mark for approved safety
- · CE-Mark





Wiha Voltage Testers. For Professionals and Do-It-Yourselfer.

Voltage Tester.





Voltage Tester, 150-250 V AC/DC.

Acc. to VDE 0680/06, DIN 57680/6, GS-Mark.

Blade:

Slotted blade, 55 mm long.

Blade insulation made of transparent cellulose acetate.

Handle: Impact resistant cellulose acetate, transparent with clip. Application: For both DIY and industrial purposes.

Order-No.		D :	=-	==	-+	_	
00451 4	in pouch	3.0	55	140	16	10	Dogri
05269 0		3.0	55	140	16	10	





Voltage Tester, 150-250 V AC/DC.

Acc. to VDE 0680/06, DIN 57680/6, GS-Mark.


Slotted blade, 65 mm long. Blade:

Blade insulation made of transparent cellulose acetate.


Handle: Impact resistant cellulose acetate, transparent with clip.

Application: For both DIY and industrial purposes.

Order-No.		Œ!	=-	==	-+		
00454 5	in pouch	3.0	65	140	15	10	108-753
05271 3		3.0	65	140	15	10	







Acc. to VDE 0680/06, DIN 57680/6, GS-Mark.

Slotted blade, 100 mm long. Blade:

Blade insulation made of transparent cellulose acetate.

Impact resistant cellulose acetate, transparent. Handle:

Application: For both DIY and industrial purposes.

Order-No.		D :	===				
004538	in pouch	3.5	100	190	18	10	103-754
05270 6					18		





Voltage Tester, 150-250 V AC/DC.

Acc. to VDE 0680/06, DIN 57680/6, GS-Mark.

Blade: Slotted blade, 100 mm long.

Blade insulation made of black cellulose acetate.

Handle: Impact resistant cellulose acetate, black with clip.

Application: For both DIY and industrial purposes.

Order-No.	Œ!	=-	==	-+		
00456 9	3.0		165		10	

Voltage & Automotive Circuit Tester.



255 -8 Voltage Tester, 150-250 V AC/DC.

Acc. to VDE 0680/06, DIN 57680/6, GS-Mark.

Blade: Slotted blade, 100 mm long.

Blade insulation made of black cellulose acetate.

Handle: Impact resistant cellulose acetate, black. Application: For both DIY and industrial purposes.

Order-No.	Œ!	==	==	-÷		
00457 6	3.5	100	185	19	10	831-591



Two-pole Voltage Tester, 125-380 V AC/DC.

Acc. to VDE 0680/06, DIN 57680/6, GS-Mark.

With dual insulated probes and 2 LEDs.

LED display lights up when voltage is detected.

Application: For AC/DC voltage.

Extra: Storage pouch supplied.

Order-No. 00452 1



€ GS

Automotive Circuit Tester, 6-24 V DC.

With attached alligator clip. Sharp point to penetrate

low-voltage wire.

Full copper material, nickel-plated.

Replacement bulb. Application: For AC/DC voltage.

Extra: Storage pouch supplied.

Order-No.		== 4	
00468 2 -4	24 Volt	120	10
00472 9 -24	Replacement bulb 24 V		10