NOTES

DESIGNED TO MEET THE REQUIREMENTS OF IP65, & NEMA 4X
TONGUE & GROOVE CONSTRUCTION WITH A MOLDED ONE PIECE SILICON GASKET.
COMES WITH 4 STAINLESS STEEL MACHINE LID SCREWS, CAPTIVATED WITH 4 RUBBER O-RINGS.
COMES WITH 4 GROUNDING SCREWS AND WASHERS.
FINISH: NONE OR SUFFIX "BK" BLACK, OR SUFFIX "GY" GRAY (RAL 7001) POLYESTER POWDER



For the best fit print on legal size paper.

THIS DRAWING IS PROPRIETARY INFORMATION OF HAMMOND MFG.CO.LTD. NOT TO BE USED WITHOUT EXPRESSED WRITTEN PERMISSION OF HAMMOND MFG.CO.LTD.

Rev	ECN	Description		Date	By
△	N/A	RELEASE	----	10/03/02	MJM

Unless otherwise spec'd dimensions are in millimeters Tolerances are:

.X	±2.5
.XX	±1.50
.XXX	±.500
.XXXX	±.1300
Holes	±.1300
Angles	±.5°

Dwn	M. MERCER
Date	10/03/02
Chk	---
Mat'l	CAST ALUMINUM
Sheet	1 of 1

HAMMOND MANUFACTURING CO. LTD.
Electronics Group, Waterloo, Ont. - Cheektowaga, NY

HAMMOND 1590Z SERIES CASTED AL ENCLOSURES

Part #: 1590Z162 | Dwg: 1590Z162/A