FEATURES AND SPECIFICATIONS



PowerCat FTP Euromod Module Category 5E

Features and Benefits

The Euromod modular system provides a flexible and versatile method of installation. This modular system offers a wide range of wallplates and modules that allow the user to install as many data outlets as required. The PowerCat module is a fully assmebled unit featuring the Molex Premise Networks low profile FTP Category 5, RJ45 RJLP connector and a 25 x 50mm fascia, shutter and spring assembly.

Molex Premise Networks unique patented RJLP RJ45 connector is engineered to meet the highest performance standards in the industry and offers a low profile, space saving design that enables installation in shallow backboxes and trunking. The FTP RJLP connector provides continuity of the cable shield by the inclusion of a termination point for the drain wire.

Suitable for high speed data transmission the PowerCat RJLP RJ45 connector was designed to meet the requirements of the Category 5E standard which demands compliance with the PowerSum principle of measurement and test.

- Category 5E RJLP connector
- EIA 568B wired
- Space saving low profile module
- Provides through shield continuity

Technical Information

Termination Tools:

Molex and other industry standard installation tools

IDC Terminations

Suitable for 0.4mm - 0.6mm solid or stranded cable, maximum o.d 1.5mm Two wires may be terminated for daisy-chain applications.

Patents pending on connector and module designs.

Mechanical

Jack Connector Operating Life : Contact Material : Contact Plating :

Minimum 500 insertion cycles Phosphor Bronze 1.25 micrometres Au/Ni UL 94VO Thermoplastic


IDC Connector

Material :

Operating Life :Minimum 100 ReterminationsContact Material :Phosphor BronzeContact Plating :Sn/Pb over NiWire Accommodation :2 x 22-26 AWG solid or stranded

Electrical

D.C. Resistance :		<20m Ω	
D.C. Resistance Imbalance :		<2.0m Ω	
Insulation Resistance :		$>100M\Omega$	
Attenuation (dB)	@	1MHz	0.0121
	@	16MHz	0.0193
	@	100MHz	0.1052
Crosstalk (dB)	@	1MHz	-84.26
	@	16MHz	-60.03
	@	100MHz	-45.70
PowerSum Worst Pair	@	100MHz	-41.83
Return Loss (dB)	@	1MHz	-65
	@	16MHz	-48
	@	100MHz	-30



Order No. Description	
MEU-00020-02 PowerCat FTP Euromod RJLP module. RJ45, 568B, Cat 5E (White)	

Molex Premise Networks standard fascia colour is white. Other colours may be subject to minimum order quantities.

Molex Premise Networks Corporate Headquarters Tel: 603 324 0200 www.molexpn.com Western Europe Headquarters Tel: 44 (0) 1489 572111 www.molexpn.co.uk

MOLEX PREMISE NETWORKS

Eastern Europe Headquarters Tel: 48 22 36 92 51 www.molexpn.com.pl Asia Headquarters Tel: 852 2637 3759 www.molexpn.com.hk

South Pacific Headquarters Tel: 61 3 9747 8322 www.molexpn.com.au Molex Incorporated Tel: 630 969 4550 www.molex.com

© 1999, Molex Premise Networks Printed in the UK Form# MEU-00020-02* Issue 1