

# Fluke 60 Series Infrared Thermometers

**FLUKE**<sup>®</sup>

The professional's diagnostic tool



**NEW!**

**NEW!**

**NEW!**

**Fluke.** Keeping your world  
up and running.

**Check**  
[www.fluke.co.uk/applications](http://www.fluke.co.uk/applications)  
to find out more or download  
the Application Notes.



**Fluke Corporation**  
P.O. Box 9090  
Everett, WA USA 98206

**Fluke Europe B.V.**  
P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands

For more information call:  
In the U.S.A. (800) 443-5853  
or Fax (425) 446-5116  
In Europe/M-East/Africa  
+31 (0)40 2 675 200  
or Fax +31 (0)40 2 675 222  
In Canada (905) 890-7600  
or Fax (905) 890-6866  
From other countries  
+1 (425) 446-5500  
or Fax +1 (425) 446-5116

Visit us on the world wide web at:  
**<http://www.fluke.com>**

Fluke (UK) Ltd.  
52 Hurricane Way  
Norwich  
Norfolk  
NR6 6JB  
United Kingdom  
Tel.: 0207 942 0700  
Fax: 0207 942 0701  
E-mail: [industrial@uk.fluke.nl](mailto:industrial@uk.fluke.nl)

© Copyright 2004 Fluke Corporation.  
All rights reserved.  
Printed in the Netherlands 09/04  
Data subject to alteration without notice.  
Pub\_ID: 10764-eng

# Fluke 60 Series Infrared Thermometers

FLUKE®



## Point, press and read temperature

The Fluke 60 Series non-contact thermometers are the ideal professional diagnostic tools for quick and accurate temperature measurements.

These handheld tools are ideal for measuring surface temperatures of rotating, hard-to-reach, electricity live or dangerously hot targets like electrical motors and – panels, and heating and ventilation systems.

The laser sighting system guides measurements to the right target and in less than a second, the large temperature display provides a readout of the surface temperature.

### The 60 Series IR thermometers feature

- Laser guided sighting system for easy targeting with 1% accuracy
- Up to 12 points datalogging with Min, max average functions
- Up to 50:1 optical resolution
- Choice between models with fixed or adjustable emissivity
- Backlit display for easy reading in the dark
- Temperatures up to 760°C

## Features

	61	63	65	66	68
Form factor	Flat grip	Pistol grip	Flat grip	Pistol grip	Pistol grip
Temperature range	-18 to 275°C	-32 to 535°C	-40 to 500°C	-32 to 600°C	-32 to 760°C
Optical resolution	8:1	12:1	8:1	30:1	50:1
Laser beam for accurate targeting	●	●	●	●	●
Backlit LCD display	●	●	●	●	●
Use selectable °C or °F	●	●	●	●	●
MIN/MAX/AVG/DIF readings		MAX only	Min/Max/avg only	●	●
Datalogging			●	●	●
Hi/Lo Alarm				●	●
Adjustable emissivity				●	●

## Specifications

	61	63	65	66	68
Range	-18 to 275°C	-32 to 535°C	-40 to 500°C	-32 to 600°C	-32 to 760°C
Response time	< 1 second	≤ 0.5 second	<1 second	≤ 0.5 second	≤ 0.5 second
Resolution	0.2°C	0.2°C	0.1°C to 200°C, 1°C over 200°C	0.1°C	0.1°C
Repeatability	± 2% of reading or ± 2°C*	± 0.5% or ≤ ± 1°C*	± 1% of reading or ± 1°C*	± 0.5% or ≤ ± 1°C*	± 0.5% or ≤ ± 1°C*
Accuracy: (assumes ambient operating temperature of 23°C)	For targets at: -18 to -1°C: ± 3°C -1 to 275°C: ± 2% of reading or ± 2°C*	For targets at: -32 to -26°C: ± 3°C -26 to -18°C: ± 2.5°C -18 to 23°C: ± 2°C 23°C -510°C: ± 1% of reading or ± 1°C* For targets above 510°C: ± 1.5% of reading	For targets at: -40 to 0°C: ± 5°C 0 to 100°C: ± 2°C 100 to 500°C: ± 2% of reading	For targets at: -32 to -26°C: ± 3°C -26 to -18°C: ± 2.5°C -18 to 23°C: ± 2°C For targets above 23°C: ± 1% of reading or ± 1°C*	For targets at: -32 to -26°C: ± 3°C -26 to -18°C: ± 2.5°C -18 to 23°C: ± 2°C For targets above 23°C: ± 1% of reading or ± 1°C*
Typical distance to target	Up to 1m	Up to 2 m	Up to 1m	5 m	8 m
Emissivity	Fixed at 0.95	Fixed at 0.95	Fixed at 0.95	Digitally adjustable from 0.1 to 1.0 by 0.01	Digitally adjustable from 0.1 to 1.0 by 0.01

\* whichever is greater

### Battery Life:

Fluke 66 and 68:	20 hours with laser and backlight on 50%
Fluke 65:	15 hours with laser and backlight activated
Fluke 63:	10 hours with laser and backlight activated
Fluke 61:	12 hours with laser and backlight activated

### Weight:

Fluke 63, 66 and 68:	0.320 kg
Fluke 65:	0.284 kg
Fluke 61:	0.227 kg

### One year warranty

### Size (HxWxD):

Fluke 63, 66 and 68:	200 mm x 160 mm x 55 mm
Fluke 65:	185 mm x 64 mm x 38 mm
Fluke 61:	184 mm x 45 mm x 38 mm

## Accessories and Ordering Information

### Included accessories

Fluke 61, 63, 66 and 68: 9V Battery  
Fluke 63, 66 and 68: Hard carrying case  
Fluke 65: C50 Soft carrying case and 2 AA batteries

### Optional accessories

80PR-60 RTD-Temperature probe for Fluke 66 and 68  
H6 Nylon holster for Fluke 63, 66 and 68

### Ordering information

Fluke 61 Infrared Thermometer  
Fluke 63 Infrared Thermometer  
Fluke 65 Infrared Thermometer  
Fluke 66 Infrared Thermometer  
Fluke 68 Infrared Thermometer

## Recommended Accessories



80PR-60



H6