HGC1M-ORG

Orange Velcro Cup Style Heel Grounder

Bright elastic orange velcro lets you see at a glance who is wearing their heel grounders. Makes Heel Grounder Compliance easy to verify. Made in the USA, this quality grounder features a durable three layer sole, lot number, and a 24 inch multi-strand ribbon. SCC foot grounders are designed and manufactured for comfort, durability, and cost effectiveness. Our grounders are UL listed for safety and tested for electrical performance. SCC uses time-tested construction techniques including computer controlled stitching, riveting, die cutting, and heat cutting to ensure consistent performance.

Standards

Meets the requirements of ANSI/ESD S-20.20, EIA 625, MIL-STD-1686, and MIL-HDBK-263.

Specifications

Resistor: 1 megohm Color: Black

Ribbon: Multi-strand, carbon suffused nylon on polyester,

sewn in sinusoidal pattern to provide side to side

conductivity.

Elastic Velcro: 3/4" Orange Sole Interior: Non-marking Sole Exterior: <10⁵ ohms


Part Numbers

HGC1M-ORG Orange Velcro Heel Grounder, 1 meg resistor

See SCC Data Sheets for these related items:

Foot Grounder Tester

Floor Mats





How Foot Grounders Work

Foot grounders discharge static from a person to ground by connecting the person to a grounded walking surface. A conductive ribbon placed inside the wearer's shoe or sock makes electrical contact with the skin through perspiration. The ribbon is joined to a resistor which limits current should accidental exposure to electricity occur. The other end of the resistor is joined to a conductive sole. This sole contacts a grounded ESD floor mat or ESD flooring system. Foot grounders must be worn on both feet to maintain ground contact while walking.

PRODUCT DATA SHEET

Foot Grounder - Cup Style - High Visibility

PRODUCT
ORANGE VELCRO HEEL GROUNDER

ITEM NUMBER
SEE ABOVE

<u>ратаѕнеет</u> 1123-в



US and Canada: 866-722-3736

Fax: 866-722-3735 Intl: 919-774-3808 Fax: 919-774-1287

3010 Lee Avenue Sanford, NC 27330

email: info@staticcontrol.com www.**StaticControl.**com