

Hook and Loop TEXTIE®

Features and Benefits

Quick and simple to use without the need for tools they have no waste, are corrosion free, are resistant to ageing and are re-usable (up to 400 times).

Various colours are available to enable easy identification of multiple cable runs.

Application

As cables use thinner and softer insulation, and as fibre optic cables become more common there is a need for a 'soft' method of bundling. The TEXTIE®s are ideal for use on telephone cables, optical fibre and network cables up to Class 6.


Perfect for use in temporary installations such as theatre stage construction or prototype cable harnesses.



There is a wide range of private or office applications for the TEXTIE®-Series.

GTM-Series Mounts for fixing are available on request. Please contact us!

Material Data	
Material Loop	Polyamide (PA)
Material Hook	Polyethylene (PE)
Operating Temperature	-20 °C to +75 °C



TEXTIE®-Series

Technical Table

Article-No.	Type	Length (L)	Width (W)	Bundle Ø max.	Material Loop	Material Hook	Colour
130-00012	TEXTIE® S	150	12.5	45	PA	PE	Black (BK)
130-00013	TEXTIE® M	200	12.5	60	PA	PE	Black (BK)
130-00021	TEXTIE® M	200	12.5	60	PA	PE	White (WH)
130-00014	TEXTIE® M	200	12.5	60	PA	PE	Red (RD)
130-00016	TEXTIE® M	200	12.5	60	PA	PE	Yellow (YE)
130-00017	TEXTIE® M	200	12.5	60	PA	PE	Green (GN)
130-00018	TEXTIE® M	200	12.5	60	PA	PE	Blue (BU)
130-00019	TEXTIE® L	330	12.5	100	PA	PE	Black (BK)
130-00020	TEXTIE® 5M	5000	12.5	–	PA	PE	Black (BK)
130-00022	TEXTIE® 25M	25000	13.0	–	PA	PE	Black (BK)

All dimensions in mm. Subject to technical changes.

Special lengths, diameters, colours and printing available on request.