

MSDS Name **DEVCON® Underwater Repair Putty (UW)**  
 Manufacturer Name ITW Devcon  
 Stock No.: 11800

<b>Components :</b>	
	UNDERWATER REPAIR PUTTY (UW) HARDENER
	UNDERWATER REPAIR PUTTY-UW RESIN
ITW Devcon Product Code : 11800	

**View MSDS :** [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#)

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** UNDERWATER REPAIR PUTTY-UW RESIN  
**Manufacturer Name:** ITW Devcon  
**Address:** 30 Endicott Street  
 Danvers, MA 01923  
**General Phone Number:** (978) 777-1100  
**Emergency Phone Number:** (800) 424-9300  
**CHEMTREC:** For emergencies in the US, call CHEMTREC : 800-424-9300  
**Canotec:** In Canada, call CANUTEC: (613) 996-6666 (call collect)  
**MSDS Revision Date:** 06/15/2009

HMIS	
Health Hazard	2*
Fire Hazard	1
REACTIVITY	1
Personal Protection	x

\* Chronic Health Effects:

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Ingredient Percent
Fillers	N/A	60 - 100 by weight
Bisphenol A diglycidyl ether resin	25068-38-6	30 - 60 by weight
Carbon black	1333-86-4	0.1 - 1 by weight
Crystalline silica	14808-60-7	0.1 - 1 by weight

**SECTION 3 - HAZARDS IDENTIFICATION**

**Emergency Overview:** WARNING! Potential Sensitizer. Irritant.  
**Route of Exposure:** Eyes. Skin. Inhalation. Ingestion.  
**Potential Health Effects:**  
**Eye:** Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury..  
**Skin:** Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.  
**Inhalation:** Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.  
**Ingestion:** Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.  
**Chronic Health Effects:** Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.  
**Signs/Symptoms:** Overexposure can cause headaches, dizziness, nausea, and vomiting.  
**Target Organs:** Eyes. Skin. Respiratory system. Digestive system.  
**Aggravation of Pre-Existing Conditions:** Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

**SECTION 4 - FIRST AID MEASURES**

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.  
**Skin Contact:** Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.  
**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.  
**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

## SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:	>400°F (204.4°C)
Flash Point Method:	Pensky-Martens Closed Cup
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO <sub>2</sub> ) or dry chemical when fighting fires involving this material.
Unsuitable Media:	Water or foam may cause frothing.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization.. Heating above 300 deg F in the presence of air may cause slow oxidative decomposition and above 500 deg F may cause polymerization.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.
Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Other Precautions:	Pump or shovel to storage/salvage vessels.

## SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling.

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

### EXPOSURE GUIDELINES

#### Carbon black :

Guideline ACGIH: 3.5 mg/m<sup>3</sup>  
TLV-TWA: 3.5 mg/m<sup>3</sup>

#### Crystalline silica :

Guideline ACGIH: 0.025 mg/m<sup>3</sup>  
TLV-TWA: 0.025 mg/m<sup>3</sup> Respirable fraction (R)

Guideline OSHA : [10 mg/m3][{% SiO2} + 2]  
Notes : Only established PEL and TLV values for the ingredients are listed.

## SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Paste..  
Color: Black.  
Odor: slight odor  
Boiling Point: >500°F (260°C)  
Melting Point: Not determined.  
Specific Gravity: 1.5  
Solubility: negligible  
Vapor Density: >1 (air = 1)  
Vapor Pressure: 0.03 mmHg @171°F  
Percent Volatile: 0  
Evaporation Rate: <<1 (butyl acetate = 1)  
pH: Neutral.  
Molecular Formula: Mixture  
Molecular Weight: Mixture  
Flash Point: >400°F (204.4°C)  
Flash Point Method: Pensky-Martens Closed Cup  
Auto Ignition Temperature: Not determined.  
VOC Content: 0 g/L  
Percent Solids by Weight 100

## SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.  
Hazardous Polymerization: Not reported.  
Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Heating resin above 300 F in the presence of air may cause slow oxidative decomposition.  
Incompatible Materials: Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines).

## SECTION 11 - TOXICOLOGICAL INFORMATION

RTECS Number: SL6480000  
**Carbon black :**  
RTECS Number: FF5800000  
Skin: Oral - Rat LD50: >15400 mg/kg [Behavioral - Somnolence (general depressed activity)]  
Administration onto the skin - Rabbit LD50: >3 gm/kg [Details of toxic effects not reported other than lethal dose value.]  
Ingestion: Oral - Rat LD50: >15400 mg/kg [Behavioral - Somnolence (general depressed activity)]  
Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans.  
**Crystalline silica :**  
RTECS Number: VV7330000  
Carcinogenicity: IARC: Group 1: Carcinogenic to humans.  
NTP: Reasonably anticipated to be a human carcinogen.

## SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.  
Environmental Fate: No environmental information found for this product.

## SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.  
RCRA Number: None.

**SECTION 14 - TRANSPORT INFORMATION**

DOT Shipping Name: Non regulated.  
 DOT UN Number: N/A  
 DOT Hazard Class: Not applicable.  
 DOT Packing Group: Not applicable.

**SECTION 15 - REGULATORY INFORMATION**

**Bisphenol A diglycidyl ether resin :**

TSCA Inventory Status: Listed  
 Canada DSL: Listed

**Carbon black :**

TSCA Inventory Status: Listed  
 California PROP 65: Listed: cancer  
 Massachusetts: Listed  
 Pennsylvania: Listed  
 Canada DSL: Listed

**Crystalline silica :**

TSCA Inventory Status: Listed  
 Massachusetts: Listed  
 Pennsylvania: Listed  
 Canada DSL: Listed

Canadian Regulations. WHMIS Hazard Class(es): D2B; D2A  
 All components of this product are on the Canadian Domestic Substances List.

**SECTION 16 - ADDITIONAL INFORMATION**

HMIS Fire Hazard: 1  
 HMIS Health Hazard: 2\*  
 HMIS Reactivity: 1  
 HMIS Personal Protection: x  
 MSDS Revision Date: 06/15/2009  
 MSDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment.

Copyright© 1996-2009 [Actio Software Corporation](#). All Rights Reserved.

**View MSDS :**    **1**   **2**   **3**   **4**   **5**   **6**   **7**   **8**   **9**   **10**   **11**   **12**   **13**   **14**   **15**   **16**

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

Product Name: **UNDERWATER REPAIR PUTTY (UW) HARDENER**  
 Manufacturer Name: ITW Devcon  
 Address: 30 Endicott Street  
 Danvers, MA 01923  
 General Phone Number: (978) 777-1100  
 Emergency Phone Number: (800) 424-9300  
 CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300  
 Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)  
 MSDS Revision Date: 06/15/2009

HMIS	
Health Hazard	3*
Fire Hazard	1
REACTIVITY	1
Personal Protection	x

\* Chronic Health Effects:

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Ingredient Percent
2,4,6-Tris (Dimethylaminomethyl)phenol	90-72-2	5 - 10 by weight
Trade secret.	N/A	30 - 60 by weight
Fillers	N/A	10 - 30 by weight
Inert material	N/A	10 - 30 by weight

### SECTION 3 - HAZARDS IDENTIFICATION

<b>Emergency Overview:</b>	WARNING! Harmful. Potential Sensitizer. Irritant.
<b>Route of Exposure:</b>	Eyes. Skin. Inhalation. Ingestion.
<b>Potential Health Effects:</b>	
<b>Eye:</b>	Can cause severe eye irritation and burns. Eye contact may cause permanent damage or blindness.
<b>Skin:</b>	Causes severe skin irritation. May cause permanent skin damage. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
<b>Inhalation:</b>	Vapor or mist may cause severe respiratory system irritation. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
<b>Ingestion:</b>	Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
<b>Chronic Health Effects:</b>	Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
<b>Signs/Symptoms:</b>	Overexposure may cause eye watering or discomfort, redness and swelling.
<b>Target Organs:</b>	Eyes. Skin. Respiratory system. Digestive system.
<b>Aggravation of Pre-Existing Conditions:</b>	Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

### SECTION 4 - FIRST AID MEASURES

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
<b>Skin Contact:</b>	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
<b>Ingestion:</b>	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

### SECTION 5 - FIRE FIGHTING MEASURES

<b>Flammable Properties:</b>	Class III B.
<b>Flash Point:</b>	>200°F (93.3°C)
<b>Flash Point Method:</b>	Estimated.
<b>Auto Ignition Temperature:</b>	Not determined.
<b>Lower Flammable/Explosive Limit:</b>	Not determined.
<b>Upper Flammable/Explosive Limit:</b>	Not determined.
<b>Fire Fighting Instructions:</b>	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
<b>Extinguishing Media:</b>	Use carbon dioxide (CO <sub>2</sub> ) or dry chemical when fighting fires involving this material.
<b>Unsuitable Media:</b>	Water or foam may cause frothing.
<b>Protective Equipment:</b>	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

<b>Spill Cleanup Measures:</b>	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.
<b>Personnel Precautions:</b>	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
<b>Environmental Precautions:</b>	Avoid runoff into storm sewers, ditches, and waterways.
<b>Other Precautions:</b>	Pump or shovel to storage/salvage vessels.

### SECTION 7 - HANDLING and STORAGE

<b>Handling:</b>	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
------------------	--

<b>Storage:</b>	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Do not store in reactive metal containers. Keep away from acids, oxidizers.
<b>Special Handling Procedures:</b>	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
<b>Hygiene Practices:</b>	Wash thoroughly after handling.

---

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

---

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
<b>Skin Protection Description:</b>	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
<b>Respiratory Protection:</b>	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
<b>Other Protective:</b>	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

### EXPOSURE GUIDELINES

#### Crystalline silica :

<b>Guideline ACGIH:</b>	0.025 mg/m <sup>3</sup> TLV-TWA : 0.025 mg/m <sup>3</sup> Respirable fraction (R)
<b>Guideline OSHA:</b>	[10 mg/m <sup>3</sup> ]/[% SiO <sub>2</sub> ] + 2]
<b>Notes :</b>	Only established PEL and TLV values for the ingredients are listed.

---

## SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

---

<b>Physical State Appearance:</b>	Paste..
<b>Color:</b>	Viscous. White.
<b>Odor:</b>	Ammonia like.
<b>Boiling Point:</b>	Not determined.
<b>Melting Point:</b>	Not determined.
<b>Specific Gravity:</b>	1.48
<b>Solubility:</b>	negligible
<b>Vapor Density:</b>	>1 (air = 1)
<b>Vapor Pressure:</b>	<1 mmHg @25°F
<b>Percent Volatile:</b>	0
<b>Evaporation Rate:</b>	Not determined.
<b>pH:</b>	10.5 @ 5 Percent Solution
<b>Molecular Formula:</b>	Mixture
<b>Molecular Weight:</b>	Mixture
<b>Flash Point:</b>	>200°F (93.3°C)
<b>Flash Point Method:</b>	Estimated.
<b>Auto Ignition Temperature:</b>	Not determined.
<b>VOC Content:</b>	0 g/L
<b>Percent Solids by Weight</b>	100

---

## SECTION 10 - STABILITY and REACTIVITY

---

<b>Chemical Stability:</b>	Stable under normal temperatures and pressures.
<b>Hazardous Polymerization:</b>	Not reported.
<b>Conditions to Avoid:</b>	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.
<b>Incompatible Materials:</b>	Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.

---

## SECTION 11 - TOXICOLOGICAL INFORMATION

---

**2,4,6-Tris (Dimethylaminomethyl)phenol :**

RTECS Number: SN3500000  
Eye: Eye - Rabbit Standard Draize Test.: 50 ug/24H [severe]  
Skin: Oral - Rat LD50 : 1200 mg/kg [Peripheral Nerve and Sensation - Flaccid paralysis without anesthesia (usually neuromuscular blockage) Lungs, Thorax, or Respiration - Dyspnea]  
Administration onto the skin - Rat LD50 : 1280 mg/kg [Details of toxic effects not reported other than lethal dose value.]  
Ingestion: Oral - Rat LD50 : 1200 mg/kg [Peripheral Nerve and Sensation - Flaccid paralysis without anesthesia (usually neuromuscular blockage) Lungs, Thorax, or Respiration - Dyspnea]

**Crystalline silica :**

RTECS Number: VV7330000  
Carcinogenicity: IARC: Group 1: Carcinogenic to humans.  
NTP: Reasonably anticipated to be a human carcinogen.

**SECTION 12 - ECOLOGICAL INFORMATION**

Ecotoxicity: No ecotoxicity data was found for the product.  
Environmental Fate: No environmental information found for this product.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.  
RCRA Number: None.

**SECTION 14 - TRANSPORT INFORMATION**

DOT Shipping Name: Non regulated.  
DOT UN Number: N/A  
DOT Hazard Class: Not applicable.  
DOT Packing Group: Not applicable.

**SECTION 15 - REGULATORY INFORMATION**

**2,4,6-Tris (Dimethylaminomethyl)phenol :**

TSCA Inventory Status: Listed  
Canada DSL: Listed

**1,3-Propanediamine, N-[3- (tridecylcloxy) propyl]-, branched :**

TSCA Inventory Status: Listed  
Canada DSL: Listed

**Crystalline silica :**

TSCA Inventory Status: Listed  
Massachusetts: Listed  
Pennsylvania: Listed  
Canada DSL: Listed  
Canadian Regulations: WHMIS Hazard Class(es): D2B; D2A

**SECTION 16 - ADDITIONAL INFORMATION**

HMIS Fire Hazard: 1  
HMIS Health Hazard: 3\*  
HMIS Reactivity: 1  
HMIS Personal Protection: x  
MSDS Revision Date: 06/15/2009  
MSDS Author: Actio Corporation  
Disclaimer: This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment.

