

Point of Sale

G81-7000 Series POS Keyboards



Main Applications

Point of Sale

- Retail
- Hospitality
- Airlines
- Postal Services
- Car Rentals

Point of Transactions/Service

- Banking
- Government
- Healthcare
- Education
- Transportation

Key Features

- Compact 16" Layout.
- Mechanical Keyswitches are Rated at 50 Million Actuations to Withstand Harsh Environments and Ensure Long Product Lifetime.
- Full US 104 Position Key Layout
- Available with PS/2 and USB Interface
- 43 Freely Programmable Keys for Easy Layout Configuration
- High Performance Magnetic Stripe Reader with Freely Programmable Headers and Terminators for Each Track
- Selection of Non-keyboard Hexcodes Enhances Security for Credit Card Processing (USB)
- Free Parsing and Configuration of Magnetic Stripe Data Stream (USB)
- Powerful 'Cherry Tools' Configuration Software Enhances Functionalities when Switching into 'Virtual Programming Mode' and Allows for Quick Product Setup & Configuration

- Easy Configuration File Transfer with Windows Explorer
- UPOS Drivers for Windows and Linux Support of Client-Server architectures
- Remote Network Installation with 'Cherry Tools' Runtime Version (USB)

Options

- 2 USB Downstream Ports (USB)
- 6&9 Pin Ports for Barcode Scanner (PS/2)
- 3-Track Magnetic Card Reader



Point of Sale

G81-7000 Series POS Keyboards

Part Number Legend





Main Part Numbers

G81-7000LPAUS-2

Black 16" PS/2 keyboard with 3-track magnetic stripe reader and 2 barcode reader ports, US 104 position key layout. Mechanical keyswitches with laser etched keycaps, 43 programmable keys. Includes Cherry Tools multifunctional configuration software and UPOS drivers.

G81-7000LUVEU-2

Black 16" USB keyboard with 3-track magnetic stripe reader, US 104 position key layout. Mechanical keyswitches with laser etched keycaps, 43 programmable keys. Includes Cherry Tools multifunctional configuration software and UPOS drivers.

G81-7000LPAUS-0

Light grey 16" PS/2 keyboard with 3-track magnetic stripe reader and 2 barcode reader ports, US 104 position key layout. Mechanical keyswitches, 43 programmable keys. Includes Cherry Tools multifunctional configuration software and UPOS drivers.

G81-7000LPDUS-0

Light grey 16" PS/2 keyboard with 3-track magnetic stripe reader, US 104 position key layout. Mechanical keyswitches, 43 programmable keys. Includes Cherry Tools multifunctional configuration software and UPOS drivers.

G81-7000LPDUS-2

Black 16" PS/2 keyboard with 3-track magnetic stripe reader, US 104 position key layout. Mechanical keyswitches, 43 programmable keys. Includes Cherry Tools multifunctional configuration software and UPOS drivers. Laser etched keys.

G81-7000LUVEU-0

Light grey 16" USB keyboard with 3-track magnetic stripe reader, US 104 position key layout. Mechanical keyswitches, 43 programmable keys. Includes Cherry Tools multifunctional configuration software and UPOS drivers.

Additional product versions on request.



Point of Sale

G81-7000 Series POS Keyboards

Technical Data

Interface

PS/2, USB 2.0

Power Consumption

max. 100 mA (PS/2) max. 400 mA (USB)

Magnetic Strip Reader

Standards:

ISO 7811/-12, AAMVA, JIS others on request

Reader head:

up to 1 million cycles

Reading speed:

3-125 inch/s at 75 Bit/inch 3-50 inch/s at 210 Bit/inch

Data is decoded to keyboard scancodes.

Barcode Ports

6-pin DIN 240 plug (right side) 9-pin SUB-D plug (right rear)

Barcode Decoding

Data is decoded to keyboard scancodes. Supported barcode formats are:

EAN/UPC, Code 39, Code 128, Codabar Interleaved 2/5, Industrial 2/5, Matrix 2/5

Code 93, Code 11, Code 16k, MSI, Plessey

Cable Length

Approx. 1.75 m

Key Layout

Full size 104 position US key layout including Windows keys

Weight (without/with packaging)
Approx. 1650/2050 kg

Dimensions

Approx. 405 x 220 x 64 mm (keyboard) Approx. 455 x 275 x 72 mm (packaging)

Packaging Units

34 keyboards per master carton 2 master cartons per pallet

Keyswitch Lifetime

>50 million operations

Storage Temperature

-20°C to 60°C

Operating Temperature

0°C to 50°C

Available Software

Cherry Tools MS Windows[™] 98, ME, 2000, XP

Cherry Tools Runtime: MS Windows[™] 98, ME, 2000, XP XP Embedded OPOS Local Edition (OLE for Point of Sale): MS Windows™ 98, ME, NT4, 2000, XP, XP Embedded

OPOS Client/Server Edition: MS Windows[™] NT4, 2000, XP, XP Embedded

JavaPOS Local Edition
(Java for Point of Sale):
MS Windows™ 98, ME, NT4, 2000,
XP, XPembedded
Suse Linux V8.0 / Kernel 2.4 or higher
IBM JRE v1.3.x and SUN JRE V1.4.x

JavaPOS Client/Server Edition:
MS Windows[™] 98, ME, NT4, 2000,
XP, XP Embedded
Suse Linux V8.0 / Kernel 2.4 or higher
IBM JRE v1.3.x and SUN JRE V1.4.x

Approvals

CE, GS, VDE, cURus, FCC, C-Tick, VCCI, BSMI (USB only) WHQL (Designed for Windows[™] 2000 and XP)

Delivery Volume

Keyboard, Manual, CDROM

Warranty

2 years

For information on repairs or warranty status contact: Cherry Technical Support Phone: 800.510.1689

E-Mail: keyboardsupport@cherrycorp.com

Contact

Call, fax or visit our website for more information.

Last Update: 3/12/08

Cherry Electrical Products

11200 88th Avenue Pleasant Prairie, WI 53158

Phone: 262.942.6500 Web: www.cherrycorp.com

E-Mail: sales@cherrycorp.com Fax: 262.942.6566 The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.