

Data Sheet

35XP-A Digital Multimeter



A compact, full-featured digital multimeter for plant maintenance, HVAC, electrical and electronic applications.

- Temperature measurement capability to 1000 °C/1832 °F (Type K thermocouple included)
- 750 V ac/1000 V dc—highest voltage rating in this class of meter
- Capacitance for motor run/start test
- 0.1 μA resolution for flame sensor testing
- Frequency to 1 MHz
- Resistance to 40 MΩ
- Data Hold freezes display
- Magne-Grip™ holster
- VolTect™ non-contact voltage detector
- Triple safety ratings

Specifications

Function	Range	Accuracy
Voltage		
DC Volts		
Ranges	400 mV, 4 V, 40 V, 400 V, 1000 V	± (0.5 % rdg + 1 dgt)
AC Volts (45 Hz to 500 Hz)		
Ranges	400 mV (45 Hz to 100 Hz) 4 V, 40 V, 400 V, 750 V	± (1.5 % rdg + 5 dgts) ± (1.5 % rdg + 5 dgts)
Resolution	100 μV	
Input Impedance	400 mV: > 100 MΩ; 4 V: 10 MΩ; 40 V to 1000 V: 9.1 MΩ	
Overload Protection	1000 V dc or 750 V ac rms	
Current		
DC Current		
Ranges	400 μA, 4000 μA, 40 mA, 400 mA 2 A	± (1.0 % rdg + 2 dgt) ± (2.0 % rdg + 3 dgts)
AC Current (45 Hz to 500 Hz)		
Ranges	400 μA, 4000 μA, 40 mA, 400 mA 2 A	± (1.5 % rdg + 5 dgts) ± (2.5 % rdg + 5 dgts)
Resolution	0.1 μA	
Input Protection	2 A/1000 V fast blow ceramic fuse 6.3 mm x 32 mm on A input	
Burden Voltage	500 mV max. (2 V max. on 4 mA, 400 mA ranges)	
Resistance		
Ranges	400 Ω, 4 kΩ, 40 kΩ, 400 kΩ, 4 MΩ 40 MΩ	± (1.0 % rdg + 4 dgts) ± (2.0 % rdg + 5 dgts)
Resolution	100 mΩ	
Open Circuit Voltage	-0.45 V dc typical, (-1.2 V dc on 400 Ω range)	
Overload Protection	1000 V dc or 750 V ac rms	
Capacitance		
Ranges	4 nF, 40 nF, 400 nF, 4 μF 40 uF, 400 uF 4 mF	± (5.0 % rdg + 30 dgts) ± (5.0 % rdg + 5 dgts) ± (5.0 % rdg + 15 dgts)
Resolution	1 pF	
Test Voltage	< 1 V	
Test Frequency	1.3 Hz on 4 nF to 40 μF ranges, 0.7 Hz on 400 μF, 4 mF ranges	
Input Protection	2 A/1000 V fast blow ceramic fuse 6.3 mm x 32 mm on A input	
Temperature		
Ranges	400 °C, 1000 °C, 400 °F, 1832 °F -20 °C to 10 °C 10 °C to 200 °C 200 °C to 1000 °C -4 °F to 50 °F 50 °F to 400 °F 400 °F to 1832 °F	± (2.0 % rdg + 4 °C) ± (1.0 % rdg + 3 °C) ± (3.0 % rdg + 2 °C) ± (2.0 % rdg + 8 °F) ± (1.0 % rdg + 6 °F) ± (3.0 % rdg + 4 °F)
Resolution	0.1 °C, 0.1 °F	
Overload Protection	1000 V dc or 750 V ac rms	



Specifications *cont.*

Function	Range	Accuracy
Frequency	4 k, 40 k, 400 k, 1 M	± (0.1 % rdg + 3 dgts)
Resolution	1 Hz	
Sensitivity	10 Hz to 1 MHz: >2.5 V rms	
Minimum Pulse Width	> 25 ns	
Duty Cycle Limits	> 30 % and < 70 %	
Overload Protection	1000 V dc or 750 V ac rms	
Continuity		
Audible Indication	Less than 25 Ω	
Response Time	100 ms	
Overload Protection	1000 VDC or 750 VAC rms	
Diode Test		
Test Current	1.2 mA (approximate)	± (1.5 % rdg + 3 dgts)
Resolution	1 mV	
Open Circuit Voltage	3.0 dc typical	
Overload Protection	1000 V dc or 750 V ac rms	
Non-Contact Voltage Indicator		
Sense voltage 70 V to 600 V ac beeper chirps and big bright red LED comes on, works on all ranges		

General Specifications

Display	3-3/4 digit liquid crystal display (LCD) with a maximum reading of 3999
Polarity	Automatic, positive implied, negative polarity indication
Overrange	(OL) or (-OL) is displayed
Zero	Automatic
Low Battery Indication	The "⊕" is displayed when the battery voltage drops below the operating level
Auto Power Off	Approx. 10 minutes
Measurement Rate	2 times per second, nominal
Operating Environment	0 °C to 50 °C at <70 % R.H.
Storage Temperature	-20 °C to 60 °C, 0 to 80 % R.H. with battery removed from meter
Accuracy	Stated accuracy at 23 °C ± 5 °C, <75 % relative humidity
Temperature Coefficient	0.1 x (specified accuracy) per °C (0 °C to 18 °C, 28 °C to 50 °C)
Altitude	2000 m
Power	Single standard 9 volt battery, NEDA 1604, JIS 006P, IEC 6F22
Battery Life	150 hours typical with carbon-zinc, 300 hours typical with alkaline
Dimensions (H x W x D)	155 mm x 72 mm x 32 mm
Weight	Approx. 400 g including battery
Warranty	One-year

No waiting.

No shipping charges.

No hassle warranty

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that a Amprobe test tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.



Included Accessories

Pair of test leads (TL245), K-type thermocouple (TP255), temperature adapter (XR-TA), fuse 2 A/ 1000 V (P/N FP200), 9 V battery (installed), Magne-Grip™ Holster with magnetic hanging strap (H2-XR) and users manual.

Optional Accessories

VC30 Carrying Case
DL243C Test Lead Kit



Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
6920 Seaway Blvd.
Everett, WA 98203
tel: 877-AMPROBE

Amprobe® Test Tools Europe

P.O. Box 1186
5602 BD Eindhoven
The Netherlands