
Hardcopy to be endorsed by authorised person.

Check with Issuing Officer or SAP system for latest update.




## Rear Artwork

Hisk of fire, explosion or burns.

Do not recharge, disassemble, crush, heat above 212°F

(100°C) or incinerate.





Front Artwork



A B C

(\*\*see note no.2) 2D Barcode Type : DataMatrix ECC 200 —





2) \*\*Contents with 2D barcode

A - Battery Work Order No. (WO)

B - Monthly Battery Assembly Code (MMYR)

C - VARTÁ internal reference only



Approx. wt : 14.5 g

7	16-R275	Added Poka Yoke design in tags	2016-08-24	Jadi
6	16-R250	Added 2D barcode in printed sleeve and change cell diameter from *Ø14.6 to Ø14.6 +0.10 -0.45	2016-06-03	Jadi
5	15-R099	Change date code from MMYY to MMYR	2015-04-07	Jadi
4	15-R012	Update UR logo arccoding to latest International standard UR logo	2015-01-28	Sunil
3	R112/08	To add in printed sleeve the crossed-out wheeled bin symbol	2008-04-30	Eka
No	AO No	Revision	Date	Name

Projection :	Material : Refer to part list no: 071788			1788	Description: CR 2/3 AA S PCBD with sleeve & PC tags				
Dimension in mm	Prepare & Checked		Verified & Approval		Dwg. No :	071788	4	0	7
Tolerance : As specified	1999-	.and			211911101	071700		لٽـــــــــــــــــــــــــــــــــــــ	_
Scale : 2 : 1	1999- 08-03 Tatang			VKB Order No	: 06237 201 301				

Rights reserved to make technical changes, as a result of further depelopment, without notice. This drawing is the property of VARTA Microbattery and must not be copied or disclosed to a third party without the written consent of VARTA Microbattery.

**VARTA**