



Number of contacts	Standard	3	4	5	5	6	7	7	8	12	14	14	19	
Contact arrangement	IEC 61076-2-106	03-a	04-a	05-a	05-b	06-a	07-a	07-b	08-a	12-a	14-a	14-b	19-a	
Contact arrangement	IEC 60130-9 <sup>b</sup>	yes		no		yes		no		yes				
Rated voltage <sup>2)</sup>	IEC 60664-1	300 V (100 V)		300 V (63 V)		100 V (32 V)		300 V (63 V)		100 V (32 V)		150 V (32 V) 60 V (32 V)		
Rated voltage	UL 1977	250V										60V		
Rated impulse withstand voltage <sup>2)</sup>	IEC 60664-1	1500 V (1500 V)		1200 V (800 V)		1500 V (1500 V)		1200 V (800 V)						
Pollution degree <sup>2)</sup>	IEC 60664-1	1 (3 <sup>3)</sup> )												
Installation category	IEC 60664-1	I												
Insulation group	IEC 60664-1	II, 400 ≤ CTI < 600												
Current rating	IEC 60512-5-2 UL 1977	10A/+40°C			7A/+40°C						3A/+40°C			
Insulation resistance	IEC 60512-3-1	>10 <sup>10</sup> Ohm <sup>4)</sup>												
Contact resistance	IEC 60512-2-1	<5mOhm												
Climatic category	IEC 60668-1	40 / 100 / 56												
Temperatur range	IEC 60668-1	-40°C...+100°C / -40°F...+212°F												
Salt spray resistance	DIN IEC 60068-2-11, test Ka	720h												
IP degree	IEC 60529	IP 69K / IP 67 / IP 65 (in mated condition)												
Insertion and withdrawal force	IEC 60512-13-2	25N	30N	35N	35N	50N	55N	55N	60N	50N	50N	50N	60N	
mechanical operation	IEC 60512-9-1	Silver ≥500 mating cycles / Gold ≥1000 mating cycles												
housing material		brass and / or zinc die cast, nickel plated												
dielectric material		thermoplastic												
sealing material		Chloroprene												
contacts		silver or gold plated												
termination technique		solder												
wire gauge		≤0,5mm <sup>2</sup> / 20 AWG						≤0,35mm <sup>2</sup> / 22 AWG						
flamability		UL 94 V0												
locking system	IEC 60130-9 DIN EN 61076-2-106	metal screw coupling; tightening torque 0,7 - 1,5 Nm												

	19 (19-a)	C091 31D019 101 2 U	C091 31D019 201 2 U
	14 (14-b)	C091 31D114 101 2 U	C091 31D114 201 2 U
	14 (14-a)	C091 31D014 101 2 U	C091 31D014 201 2 U
	12 (12-a)	C091 31D012 101 2 U	C091 31D012 201 2 U
	8 (08-a)	C091 31D008 101 2 U	C091 31D008 201 2 U
	7 (07-b)	C091 31D107 101 2 U	C091 31D107 201 2 U
	7 (07-a)	C091 31D007 101 2 U	C091 31D007 201 2 U
	6 (06-a)	C091 31D006 101 2 U	C091 31D006 201 2 U
	5 (05-b)	C091 31D105 101 2 U	C091 31D105 201 2 U
	5 (05-a)	C091 31D005 101 2 U	C091 31D005 201 2 U
	4 (04-a)	C091 31D004 101 2 U	C091 31D004 201 2 U
	3 (03-a)	C091 31D003 101 2 U	C091 31D003 201 2 U
<b>Contact arrangement View on mating side</b>	<b>Number of contacts (Contact arrangement acc. IEC 61076-2-106)</b>	<b>Part number-Ag</b>	<b>Part number-Au</b>

Gewicht (errechnet) / Calc WT: 0,041 kg		Zul. Abw./Tolerances:		Maßstab / Scale: 2:1		A3			
Prüfmaß / Testdimension		ISO 2768-c		CUSTOMER DRAWING		1		Blatt / Sheet	
Teileindex / Partindexnumber:		DIN / ISO 13715							
Bagatelle change:		Gez. 08.06.2017		Female cable connector for cable diameter 6-8mm		1		Blatt / Sheet	
		Drawn AZN_NPFEIFFE							
		Status Released							
		Gepr. 11.01.2021		M C091 31DXXX X01 2 U		1 Bl.		NXXM-V03	
		Checked MBERTSCH							
04	202000083	27.10.2020	MCARL	Amphenol Tuchel Industrial GmbH		Ers. f. l. Replacement for: M-C091 31DXXX X01 2 Rev02			
03	201700004	12.06.2017	NPFEI						
Index	Änderung / Description	Datum / Date	Name						

<sup>1)</sup> Edition 2000-05  
<sup>2)</sup> values in brackets are according to DIN EN 61076-2-106  
<sup>3)</sup> designed acc. pollution degree 2, can be used under pollution degree 3 when the rules of IEC 60644-1 are fulfilled  
<sup>4)</sup> under operating conditions >10<sup>8</sup> Ohm  
 Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground.  
 Remark for gold plated contacts:  
 In order to avoid brittle inter-metallic connections, gold plated terminals have to be tin-plated in the solder area.  
 All technical data have been measured in a laboratory environment and can be different during practical usage of the product. Any product information is for descriptive usage only and not legally binding, particularly the information does not constitute or provide any legal guaranties ("Beschaffenheitsgarantie" or "Haltbarkeitsgarantie").

Coping of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of the utility model or design.  
 Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

FAI2020-003266