



FOR BACK MOUNT USE SCREWS 7mm + PANEL THICKNESS MAXIMUM LENGTH.



VARIANTS	
PART NO.	HOLE DETAILS
CP303080	HOLE Ø3.50xCSK 82°x Ø5.85
CP303080X	PLAIN HOLE Ø2.50

CP303080X - Ø2.50 PLAIN HOLES

3rd ANGLE PROJECTION: 🕀 🛑



RoHS. **▼**COMPLIANT

TOLERANCE

NO DEC. PLACE ±

1 DEC. PLACE ±

2 DEC. PLACE ±

HOLE Ø ±

ANGLES ±

UNLESS

OTHERWISE STATED

FOR FRONT MOUNT USE SCREWS 7mm MAXIMUM LENGTH.

NOTE:-

Cliff Electronic Components Ltd.
76 Holmethorpe Avenue, Holmethorpe Industrial Estate,
Redhill, Surrey, RH1 2PF, England, UK
Tel: 01737-771375 Fax: 01737-766012 Website: www.cliffuk.co.uk

DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE STATED. WORK TO DIMENSIONS. REMOVE ALL BURRS. IF IN DOUBT ASK

SEE TABLE MATERIAL: SEE TABLE FINISH: THE CONTENTS OF THIS DOCUMENT MUST NOT BE COPIED OR DISCLOSED NJB TO A 3rd PARTY WITHOUT WRITTEN PERMISSION OF CLIFF UK. © 2018 DRAWN: APPROVED: DPJ

TITLE: XRP3 S4/BBB/ST

CP303080 DRWG. No.

DO NOT SCALE

FORM: A4DRWGH