



OPENING

Features:

- Arm Band Badge Holder
 - Material Thickness:

0.012" (2S) front pocket & 0.036" (2S) back

Material Tolerance (thickness):

±10%

- Ideal for use by electronic manufacturers working with ESD sensitive components.
- Made with a custom dissipative material made exclusively for Desco Industries
- Rtt: 1 x 10⁶ to < 1 x 10¹⁰ ohms per ANSI/ESD STM11.11
- Tribocharging: Less than 100 volts
- ESD symbol allows people to immediately know the Badge Holder has ESD control properties: low charging antistatic and dissipative
- · Perfect for active personnel if standard badges fall off their clothing
- 4" x 4 5/16" (Outer Dimension), 2 3/8" x 3 3/8" (Insert Size)
- Adjustable black elastic band flexes with arm movement for secure fit
- Made in the United States of America

Item Description

35193 Clear Arm Band Badge Holder, Black Elastic Band

± 1/16" tolerances on dimensions unless specified.

Specifications and procedures subject to change without notice.

ARM BAND ESD BADGE HOLDER, 2-3/8" x 3-3/8" INSERT SIZE

3651 WALNUT AVENUE, CHINO, CA 91710	
PHONE: (909) 627-2453	
WEBSITE: Menda-ID.com	

DRAWING	DATE
NUMBER	October
35193	2013

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20 section 2.4 Sources of Static Electricity]

