DATA SHEET: TPB14 SERIES



LED Bulkhead



+ SensorwithFinishes available:WhiteWeight (kg):1.51.25Wattage (W):14.2Lumens (lm):1020Efficacy lm/W:71P.F:0.8Beam Angle:110°Overall dimensions (mm):330 (d) 110	D Bulkhead th EM	LED Bulkhead EM + sensor		
Finishes available: Weight (kg): 1.5 Wattage (W): Lumens (lm): Efficacy lm/W: P.F: 0.8 Beam Angle: 110° Overall dimensions (mm): CCT: 6000K LED colours: Dayligh Input Voltage: Mains 230V Initial charge time: N/A N/A N/A		EM + sensor		
Weight (kg): 1.5 Wattage (W): 14.2 Lumens (lm): 1020 Efficacy lm/W: 71 P.F: 0.8 Beam Angle: 110° Overall dimensions (mm): 330 (d) 110 (d)	1.8			
Wattage (W): Lumens (Im): Efficacy Im/W: P.F: 0.8 Beam Angle: 110° Overall dimensions (mm): CCT: 6000K LED colours: Input Voltage: Input Voltage: N/A N/A N/A	1.8	White		
Lumens (lm):1020Efficacy lm/W:71P.F:0.8Beam Angle:110°Overall dimensions (mm):330 (d) 110		1.35		
Efficacy lm/W: 71 P.F: 0.8 Beam Angle: 110° Overall dimensions (mm): 330 (d) 110 (cct.) CCT: 6000K LED colours: Dayligh Input Voltage: Mains 230V Initial charge time: N/A N/A Discharge duration: N/A N/A				
P.F: Beam Angle: Overall dimensions (mm): CCT: 6000K LED colours: Input Voltage: Initial charge time: N/A N/A N/A				
Beam Angle:110°Overall dimensions (mm):330 (d) 110 (multiple)CCT:6000KLED colours:DaylighInput Voltage:Mains 230VInitial charge time:N/ADischarge duration:N/A				
Overall dimensions (mm):330 (d) 110 (
CCT: 6000K LED colours: Dayligh Input Voltage: Mains 230V Initial charge time: N/A N/A Discharge duration: N/A N/A				
LED colours:DaylighInput Voltage:Mains 230VInitial charge time:N/AN/ADischarge duration:N/AN/A	[p]			
Input Voltage: Mains 230V Initial charge time: N/A N/A Discharge duration: N/A N/A				
Initial charge time:N/AN/ADischarge duration:N/AN/A	t			
Discharge duration: N/A N/A	50Hz			
	24Hrs	24Hrs		
	3Hrs	3Hrs		
Temperature range: -10°C to +3	-10°C to +35°C			
Battery type: N/A N/A	2000mAh 6V Ni-	-CD Battery 5 cell		
Construction: Polycarbon	iate			
Class I				
IP rating: IP44				
Warranty: 3 Years (excluding t	he battery)			
Life Span (hrs): 30,000				
Photometric data: Yes				
Dimmable: No				
Accessories available: TPB33BRG – Brass, TPB3		•		
TPB33MSRG – Matt Silver,	TPB33WHRG -	White.		
Instruction sheet: Yes				
Origin of Manufacture: China				
Quality assurance system: IS0900				



