



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

LOCTITE SI 598 BK CR300ML EGPLRU

SDS No. : 152851

V009.0

Revision: 13.10.2022

printing date: 14.10.2022

Replaces version from: 21.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SI 598 BK CR300ML EGPLRU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Silicone sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye damage

Category 1

H318 Causes serious eye damage.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Carcinogenicity

Category 1B

H350 May cause cancer.

Specific target organ toxicity - single exposure

Category 2

H371 May cause damage to organs.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Silicon compounds

2-butanone oxime

Signal word:

Danger

Hazard statement:

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H350 May cause cancer.
 H371 May cause damage to organs.

Supplemental information

Restricted to professional users.

**Precautionary statement:
Prevention**

P201 Obtain special instructions before use.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement:
Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly.

This mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Self-classification according to Article 12(b) of (EU) 1272/2008.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

| | |
|--|----------|
| octamethylcyclotetrasiloxane 556-67-2 | PBT/vPvB |
|--|----------|

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|---|----------------------|--|--|-------------------------|
| Silicon compounds | 1- < 3 % | Skin Sens. 1, H317 Eye Dam. 1, H318 STOT RE 2, H373 | | |
| 2-butanone oxime 96-29-7 202-496-6 01-2119539477-28 | 1- < 3 % | STOT SE 3, H336 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 Skin Sens. 1, H317 Carc. 1B, H350 Acute Tox. 3, Oral, H301 Acute Tox. 4, Dermal, H312 | dermal:ATE = 1.100 mg/kg oral:ATE = 100 mg/kg | |
| octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36 | 0,01- < 0,1 % | Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226 | M chronic = 10 | SVHC PBT/vPvB |

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.
Silicon dioxide

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.
Scrape up as much material as possible.
Sweep up spilled material. Avoid creating dust.
Store in a partly filled, closed container until disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.
See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Store in a cool, well-ventilated place.
Refer to Technical Data Sheet
Never allow product to get in contact with water during storage

7.3. Specific end use(s)

Silicone sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|------------------------------|--|-----------------|
| Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, RESPIRABLE DUST] | | 2,4 | Time Weighted Average (TWA): | | EH40 WEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, INHALABLE DUST] | | 6 | Time Weighted Average (TWA): | | EH40 WEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [Dust, inhalable dust] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [Dust, respirable dust] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|------------------------------|--|-----------------|
| Limestone 1317-65-3 [CALCIUM CARBONATE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Limestone 1317-65-3 [CALCIUM CARBONATE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [DUSTS NON-SPECIFIC] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS] | | 2,4 | Time Weighted Average (TWA): | | IR_OEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS] | | 6 | Time Weighted Average (TWA): | | IR_OEL |
| Silane, dichlorodimethyl-, reaction products with silica | | 4 | Time Weighted Average (TWA): | | IR_OEL |

| | | | | | |
|--|----|----|-----------------------------------|------------|--------|
| 68611-44-9 [DUSTS NON-SPECIFIC] | | | | | |
| Butanone oxime 96-29-7 [METHYL ETHYL KETOXIME] | 3 | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Butanone oxime 96-29-7 [METHYL ETHYL KETOXIME] | 10 | 33 | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|------------------------------|-----------------|--------------|-----|------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Octamethylcyclotetrasiloxane 556-67-2 | aqua (freshwater) | | 0,0015 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | aqua (marine water) | | 0,00015 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sediment (freshwater) | | | | 3 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sediment (marine water) | | | | 0,3 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | oral | | | | 41 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | Soil | | | | 0,54 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|--------------------|-------------------|---------------------------------------|---------------|-----------|---------|
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - systemic effects | | 73 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - local effects | | 73 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - systemic effects | | 13 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - local effects | | 13 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | oral | Long term exposure - systemic effects | | 3,7 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Dust mask, P2 particle filter.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | solid |
| Delivery form | Currently under determination |
| Colour | black |
| Odor | mild |
| Melting point | Not available. |
| Solidification temperature | Not applicable, Product is a solid. |
| Initial boiling point | Not applicable |
| Flammability | Currently under determination |
| Explosive limits | Currently under determination |
| Flash point | > 93 °C (> 199.4 °F); Tagliabue closed cup |
| Auto-ignition temperature | Not applicable, Product is a solid. |
| Decomposition temperature | Currently under determination |
| pH | Not applicable, Product is non-soluble (in water). |
| Viscosity (kinematic) | Not applicable, Product is a solid. |
| Solubility (qualitative) | Polymerises in presence of water. |
| (Solvent: Water) | |
| Partition coefficient: n-octanol/water | Currently under determination |
| Vapour pressure (20 °C (68 °F)) | < 5 mm hg |
| Density () | 1,05 g/cm ³ None |
| Relative vapour density: | Heavier than air. |
| Particle characteristics | Currently under determination |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with oxidants, acids and lyes

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Excessive heat.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

General toxicological information:

Methylethyl ketoxime released during polymerisation of oxime curing RTV silicones is irritating to the respiratory system

Methylethyl ketoxime released during polymerisation of oxime curing silicones. It is harmful in contact with skin and is a skin sensitizer.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|--|---------------|---------|---|
| Silicon compounds | LD50 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 2-butanone oxime 96-29-7 | Acute toxicity estimate (ATE) | 100 mg/kg | | Expert judgement |
| octamethylcyclotetrasiloxane 556-67-2 | LD50 | > 4.800 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|--|---------------|---------|---|
| Silicon compounds | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| 2-butanone oxime 96-29-7 | Acute toxicity estimate (ATE) | 1.100 mg/kg | | Expert judgement |
| octamethylcyclotetrasiloxane 556-67-2 | LD50 | > 2.375 mg/kg | rat | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|--|---------------|-----------|-----------------|------------------|---------------|--|
| 2-butanone oxime 96-29-7 | LC50 | > 20 mg/l | not specified | 4 h | not specified | not specified |
| octamethylcyclotetrasiloxane 556-67-2 | LC50 | 36 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------|------------------|---------|---|
| octamethylcyclotetrasiloxane 556-67-2 | not irritating | | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|---|------------------|---------|--|
| 2-butanone oxime 96-29-7 | Category 1 (irreversible effects on the eye) | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| octamethylcyclotetrasiloxane 556-67-2 | not irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|--|-----------------|------------------------------|------------|---|
| Silicon compounds | sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| 2-butanone oxime 96-29-7 | sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| octamethylcyclotetrasiloxane 556-67-2 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|---|--|----------------------------|---|
| Silicon compounds | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2-butanone oxime 96-29-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | EPA OPPTS 870.5265 (The Salmonella typhimurium Bacterial Reverse Mutation Test) |
| 2-butanone oxime 96-29-7 | negative | mammalian cell gene mutation assay | with | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 2-butanone oxime 96-29-7 | negative | DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro | | | OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | bacterial gene mutation assay | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | in vitro mammalian chromosome aberration test | with and without | | equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Silicon compounds | negative | intraperitoneal | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| 2-butanone oxime 96-29-7 | negative | oral: gavage | | rat | EPA OPPTS 870.5385 (In Vivo Mammalian Cytogenetic Tests: Bone Marrow Chromosomal Analysis) |
| 2-butanone oxime 96-29-7 | negative | oral: feed | | Drosophila melanogaster | EPA OPPTS 870.5385 (In Vivo Mammalian Cytogenetic Tests: Bone Marrow Chromosomal Analysis) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | inhalation | | rat | equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|---------------------------------|--------------|-------------------------|---|---------|------|---------------------------------------|
| 2-butanone oxime 96-29-7 | carcinogenic | inhalation: vapour | 3 - 18 m 6 h/d, 5 d/w | mouse | male | EPA OTS 798.3300 (Carcinogenicity) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|--|--|-----------------------------|-------------------------|---------|--|
| 2-butanone oxime 96-29-7 | NOAEL F1 >= 200 mg/kg NOAEL F2 >= 200 mg/kg | Two generation study | oral: gavage | rat | not specified |
| octamethylcyclotetrasiloxane 556-67-2 | NOAEL P 300 ppm NOAEL F1 300 ppm | two- generation study | inhalation | rat | equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|--|-----------------|-------------------------|--|---------|---|
| Silicon compounds | NOAEL 10 mg/kg | oral: gavage | | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| 2-butanone oxime 96-29-7 | LOAEL 40 mg/kg | oral: gavage | 13 w 5 d/week | rat | EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents) |
| octamethylcyclotetrasiloxane 556-67-2 | LOAEL 35 ppm | inhalation | 6 h nose only inhalation 5 days/week for 13 weeks | rat | OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day) |
| octamethylcyclotetrasiloxane 556-67-2 | NOAEL 960 mg/kg | dermal | 3 w 5 d/w | rabbit | equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Self-classification according to Article 12(b) of (EU) 1272/2008.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|--|--|
| 2-butanone oxime 96-29-7 | LC50 | 320 - 1.000 mg/l | 96 h | Leuciscus idus | DIN 38412-15 |
| 2-butanone oxime 96-29-7 | NOEC | 50 mg/l | 14 d | Oryzias latipes | OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 0,0044 mg/l | 93 d | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OPPTS 797.1600 (Fish Early Life Stage Toxicity Test) |
| octamethylcyclotetrasiloxane 556-67-2 | LC50 | Toxicity > Water solubility | 96 h | Oncorhynchus mykiss | EPA OTS 797.1400 (Fish Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|---------------|---|
| 2-butanone oxime 96-29-7 | EC50 | > 500 mg/l | 48 h | Daphnia magna | EU Method C.2 (Acute Toxicity for Daphnia) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|------------|---------------|---------------|--|
| 2-butanone oxime 96-29-7 | NOEC | > 100 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 7.9 µg/l | 21 d | Daphnia magna | EPA OTS 797.1330 (Daphnid Chronic Toxicity Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------------------------|---------------|--|---|
| 2-butanone oxime 96-29-7 | EC50 | 11,8 mg/l | 72 h | Scenedesmus capricornutum | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-butanone oxime 96-29-7 | NOEC | 2,56 mg/l | 72 h | Scenedesmus capricornutum | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | EPA OTS 797.1050 (Algal Toxicity, Tiers I and II) |
| octamethylcyclotetrasiloxane 556-67-2 | EC10 | 0,022 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | EPA OTS 797.1050 (Algal Toxicity, Tiers I and II) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------------------------|---------------|------------------|--|
| 2-butanone oxime 96-29-7 | EC10 | 177 mg/l | 17 h | | DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 3 h | activated sludge | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|--|----------------------------|-----------|---------------|---------------|--|
| Silicon compounds | not readily biodegradable. | aerobic | 28 % | 28 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| 2-butanone oxime 96-29-7 | inherently biodegradable | aerobic | 70 % | 14 d | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |
| octamethylcyclotetrasiloxane 556-67-2 | not readily biodegradable. | aerobic | 3,7 % | 29 d | OECD Guideline 310 (Ready Biodegradability CO ₂ in Sealed Vessels (Headspace Test)) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|--|-------------------------------|---------------|-------------|---------------------|---|
| 2-butanone oxime 96-29-7 | 0,5 - 0,6 | 42 d | 25 °C | Oryzias latipes | OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish) |
| octamethylcyclotetrasiloxane 556-67-2 | 12.400 | 28 d | | Pimephales promelas | EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout) |

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|--|--------|-------------|--|
| 2-butanone oxime 96-29-7 | 0,65 | 25 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| octamethylcyclotetrasiloxane 556-67-2 | 6,98 | 21,7 °C | other guideline: |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|--|---|
| 2-butanone oxime 96-29-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| octamethylcyclotetrasiloxane 556-67-2 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number or ID number**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable

Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content < 5,00 %
(2010/75/EC)**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H361f Suspected of damaging fertility.
H370 Causes damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2 | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.