

Smart Digital Power Meter **multicomp** PRO

**RoHS
Compliant**



Introduction

The smart digital power meter is an economic and portable measuring instrument. It is a multi-functional measuring instrument which integrating voltage, current, power, power factor, frequency and harmonic wave. The product is widely used in production, testing, evaluation and scientific research and multi-field

Features

- VA broken code screen display, reading intuitive, it adopts high speed A/D transformer and 32-bit MCU operation.
- Multi-window simultaneous display of voltage, current, power, power factor/frequency.
- Voltage, current range can switch to auto range or manual range.
- Support AC, DC, AC+DC (T-RMS) mode.
- Average function can make the reading more stable and it suitable for measuring the load or power with large variations.
- Data upgrade period can be set. User can select a faster upgrade period according to the test needs, so as to improve the test efficiency.
- Communication interface supports RS-232 and RS-485. Communication protocol supports SCPI and Modbus for communicating with computer and PLC.
- It can freely set the upper and lower limit of current and power, the digital power meter will automatic judge whether the test value is exceed. Sound and light alarm indication, it is convenient for batch detection to improve the measurement efficiency.
- This is also supports set the voltage, apparent power and set and detect the upper and lower limift of power factor.)

Specification

Model	MP701125
Display	VA broken code display, 5 digits, four windows
Display Update Rate	0.1S, 0.25S, 0.5S, 1S, 2S, 6S
Measuring Object	V,A,W,PF/Hz
Measuring Mode	AC/DC/AC+DC(T-RMS)
Measuring Range of Voltage	3V-600V
Voltage Range	75V/150V/300V/600V
Accuracy of Voltage (1%-100% of range)	DC $\pm(0.4\%$ reading+ 0.1% range+1 character) 40Hz $\leq f \leq 66$ Hz: $\pm(0.4\%$ reading +0.1% range+1 range+1 character) 66Hz $< f \leq 400$ Hz: $\pm(0.3\%$ reading 0.2% range+1 character)
Voltage Resolution	0.1V/0.1V

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp PRO

Smart Digital Power Meter

multicomp^{PRO}

Model	MP701125	
Measuring Range of Current	0.5mA-20A	
Current Range	500mA/2A/8A/20A	
Accuracy of Current (1%-100% of range)	DC $\pm(0.4\%$ reading+ 0.1% range+1 character) 40Hz $\leq f \leq 66$ Hz: $\pm(0.4\%$ reading +0.1% range+1 range+1 character) 66Hz $< f \leq 400$ Hz: $\pm(0.3\%$ reading 0.2% range+1 character)	
Current Resolution	0.1mA/1mA	
Switching Range	Auto/Manual	
Power Range	1W-12kW	
Accuracy of Power (PF1)	DC $\pm(0.4\%$ reading+ 0.1% range+1 character) 40Hz $\leq f \leq 66$ Hz: $\pm(0.4\%$ reading +0.1% range+1 range+1 character) 66Hz $< f \leq 400$ Hz: $\pm(0.3\%$ reading 0.2% range+1 character)	
Power Resolution	0.001W/0.01W/0.1W/1W	
Power Factor Range	-1.000~1.000	
Accuracy of Power Factor	$\pm(0.004+0.001^*$ reading +1 character)	
Frequency Range	DC, 40Hz-400Hz (voltage>10% of range)	
Accuracy of Frequency	$\pm(0.1\%$ reading +1 Character)	
Auto Range	Voltage Range Increasing	Urms exceeds the measuring range about 110% (CF<2)
	Voltage Range Decreasing	Urms is less than the lower part range about 80% (CF<2)
	Current Range Increasing	Irms exceeds the measuring range about 110% (CF<2)
	Current Range Decreasing	Irms is less than the lower part range about 60% (CF<2)
Pre-heating Time	>30 min	
Current Peak	The maximum display 24A	
Maximum of Allowed Input for Continuous	Voltage 700V, Current 24A	
Maximum of Allowed input for Instant	1000V. 40A (1 min)	
Input Impedance	Voltage about 2 M Ω , Current is less than 0.02 Ω	
Upper/Lower Limit	Four settings for the upper/lower limit of power and current	
	P Hi (Power high) P Lo(Power low) A Hi (Current high) A Lo (Current low)	
Average Function	√	
Harmonic Analysis	/	
Peak Measurement	/	
Display Hold	√	
Mute Alarm	√	
Mute Key	/	
Lock Key	√	

Smart Digital Power Meter

multicomp^{PRO}

Model	MP701125
Interface	RS232 (DB9 2-pin: TX, 3-pin: RX, 5-pin: GND)
	RS485 (DB9; 8-pin: A. 9-pin: B)
Baud Rate	4800, 9600, 19.2K, 38.4K , 57.6K, 115.2K, default 9600, It follows communication protocol of standard SCPI and Modbus RTU.
Power Source	Input power: AC 100V-240V Frequency 50/60Hz
Precision Environment	18°C~28°C, 30%~75%RH (28°C < operating temperature < 18°C (when in 18°C, it needs to add temperature coefficient), reading of 0.05°C)
Storage Temperature	-10°C-50°C, non-condensing below 80% RH
Operating Altitude	≤2000 meters
General Characteristic	
Color	Gray
Weight	3.3kg
Size	214mm×80mm×340mm
Standard Accessories	Specialized power cable x1; RS232 serial port line X1
Standard Packing Quantity (Outer Box)	2
Standard Packing Size	400mm × 300m × 325mm
Gross Weight of Standard Packing	9kg

Part Number Table

Description	Part Number
Smart Digital Power Meter, 600V, 20A, EU/UK	MP701125

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp^{PRO}