



Spring Loaded Connector multicomp^{PRO}

RoHS
Compliant



Housing



Housing W/Double Rows

Specification

Electrical

Current Rate : 3A
Contact Resistance : 50mΩ



Environmental

Operating temperature range : -40°C to 80°C


Material

Pin : Brass C3604, 20u" gold Plating
Housing : PA46, Black

Diagram



Housing



Housing W/Double Rows

Dimensions : Millimetres

Spring Loaded Connector **multicomp**PRO

Part Number	Row	Pin	L ±0.3	W ±0.15	H ±0.15	Pitch ±0.05	Hole ±0.05
MP015210	1	2	5.3	2.5	2.5	2.54	1.5
MP015211		3	7.8				
MP015212		4	10.2				
MP015213		5	12.8				
MP015214	2	8	10.16	5.08	2.5	2.54	
MP015215		10	12.7				

Part Number Table

Description	Part Number
2 Position 3.8mm SMT Female Pin with 2.54mm Housing	MP015210
3 Position 3.8mm SMT Female Pin with 2.54mm Housing	MP015211
4 Position 3.8mm SMT Female Pin with 2.54mm Housing	MP015212
5 Position 3.8mm SMT Female Pin with 2.54mm Housing	MP015213
8 Position 3.8mm SMT Female Pin with 2.54mm Housing With Double Row	MP015214
10 Position 3.8mm SMT Female Pin with 2.54mm Housing With Double Row	MP015215

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 sg.element14.com/b/multicomp-pro

multicompPRO