

UICIT_WMRF 8/16_KIT



Part number	09 58 024 1032
Specification	UICIT_WMRF 8/16_KIT
HARTING eCatalogue	https://b2b.harting.com/09580241032

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connector sets
Series	HARTING UIC
Identification	UIC IT
Element	Connector sets

Version

Termination method	Crimp termination
Gender	Female
Number of contacts	24
Details	Crimp contacts enclosed separatly Module enclosed separatly Cable clamp enclosed separatly

Technical characteristics

Conductor cross-section	0.09 0.52 mm² 1 mm² Signal
Conductor cross-section [AWG]	AWG 24 AWG 28 Data AWG 18 Signal
Rated current (data)	1 A
Rated voltage (data)	50 V
Rated current (signal)	10 A
Rated voltage (signal)	100 V
Transmission characteristics	Cat. 7 _A Class F _A up to 1,000 MHz Cat. 8 Class II up to 2000 MHz

Page 1 / 3 | Creation date 2024-11-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 58 024 1032 UICIT_WMRF 8/16_KIT



Technical characteristics

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
	25 Gbit/s
	10 Gbit/s
Insulation resistance	>10 ⁷ Ω
Contact resistance	≤4 mΩ
Tightening torque	5 Nm Fixing screws M6
Limiting temperature	-40 +90 °C
Mating cycles	≥10,000
Degree of protection acc. to IEC 60529	IP67 / IP69

Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Gold plated
Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 1003 (signal yellow)
Material (seal)	Silicone
Material (locking)	Stainless steel
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
California Proposition 65 substances	Not contained

Page 2 / 3 | Creation date 2024-11-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 58 024 1032 UICIT_WMRF 8/16_KIT



Specifications and approvals

Specifications	UIC 50558 IRS 50558 IEC 61373 Category 2 IEC 60529
Commercial data	
Packaging size	1
Net weight	0.7 kg
Country of origin	India
European customs tariff number	85366990
GTIN	5713140492165
ETIM	EC002635
eCl@ss	27440115 Circular connector (set)